

## 2015 Geometry - City

Models	Size	Actual Frame Size	Wheel size	Seat tube	Seat tube angle	Head tube length	Head angle	Effective top tube	Bottom bracket drop	Bottom bracket height	Chainstay length	Offset	Trail	Wheelbase	Standover	Frame reach	Frame stack
7.7 FX	50cm	50cm	700c	45.0	74.6°	13.0	71.1°	51.9	8.0		42.0	5.3	6.0	99.6	71.6	36.8	54.6
	52cm	52cm	700c	47.5	74.2°	14.5	71.3°	53.0	8.0		42.0	5.3	5.9	100.3	73.5	37.1	56.1
	54cm	54cm	700c	50.0	73.7°	16.0	71.3°	54.2	8.0		42.0	5.3	5.9	101.0	75.4	37.4	57.5
	56cm	56cm	700c	52.5	73.3°	17.5	71.9°	55.4	7.8		42.0	4.8	6.1	100.8	77.6	37.7	59.1
	58cm	58cm	700c	54.8	73.0°	19.5	72.0°	56.7	7.8		42.5	4.8	6.0	102.2	79.6	38.0	61.1
	60cm	60cm	700c	56.7	72.8°	22.0	72.1°	57.9	7.5		42.5	4.8	5.9	103.2	81.7	38.3	63.2
7.5 FX	15"	15"	700c	38.1	74.5°	11.5	70.5°	54.4		28.5	44.5	5.0	7.0	105.7	69.3		
7.4 FX & Disc	17.5"	17.5"	700c	44.4	74.0°	13.0	70.5°	54.8		28.5	44.5	5.0	7.0	105.7	73.5		
7.3 FX	20"	20"	700c	50.8	73.5°	16.0	71.5°	56.8		28.5	44.5	4.5	7.0	105.8	78.3		
7.2 FX & Disc	22.5"	22.5"	700c	57.1	73.0°	19.0	72.5°	59.0		28.5	44.5	4.5	6.2	106.4	83.1		
	25"	25"	700c	63.5	72.0°	22.0	72.5°	60.3		28.5	44.5	4.5	6.2	106.5	87.7		
7.5 FX WSD	13"	13"	700c	33.0	75.0°	11.5	70.0°	53.0		28.5	44.5	5.0	7.3	105.3	66.6		
7.4 FX WSD	15"	15"	700c	38.1	75.0°	13.0	70.5°	53.3		28.5	44.5	5.0	7.0	105.3	69.7		
7.3 FX WSD	17"	17"	700c	43.2	74.5°	15.0	70.5°	53.9		28.5	44.5	5.0	7.0	105.5	73.2		
7.2 FX WSD	19"	19"	700c	48.3	74.0°	16.0	70.5°	55.3		28.5	44.5	5.0	7.0	106.4	76.7		
	15" Stagger	15"	700c	38.1	74.5°	13.0	70.5°	54.3		28.5	44.5	5.0	7.0	105.6	62.4		
	17.5" Stagger	17.5"	700c	44.5	74.0°	15.0	70.5°	54.8		28.5	44.5	5.0	7.0	105.7	63.0		
	20" Stagger	20"	700c	50.8	73.5°	17.0	71.5°	56.8		28.5	44.5	4.5	7.0	105.7	63.3		
		22.5"	22.5"	700c	57.1	73.0°	19.0	72.5°	59.0		28.5	44.5	4.5	6.3	106.3	83.4	
7.1 FX	15"	15"	700c	38.1	74.5°	11.5	70.5°	54.4		28.5	44.5	5.0	7.1	105.6	69.7		
7.0 FX	17.5"	17.5"	700c	44.4	74.0°	13.0	70.5°	54.8		28.5	44.5	5.0	7.1	105.6	73.8		
	20"	20"	700c	50.8	73.5°	16.0	71.5°	56.8		28.5	44.5	4.5	7.0	105.7	78.6		
	22.5"	22.5"	700c	57.1	73.0°	19.0	72.5°	59.0		28.5	44.5	4.5	6.3	106.3	83.4		
	25"	25"	700c	63.5	72.0°	22.0	72.5°	60.3		28.5	44.5	4.5	6.3	106.4	88.0		
	15" Stagger	15"	700c	38.1	74.5°	13.0	70.5°	54.3		28.5	44.5	5.0	7.1	105.6	62.7		
	17.5" Stagger	17.5"	700c	44.5	74.0°	15.0	70.5°	54.8		28.5	44.5	5.0	7.1	105.7	63.2		
	20" Stagger	20"	700c	50.8	73.5°	17.0	71.5°	56.8		28.5	44.5	4.5	7.0	105.7	63.6		
	22.5" Stagger	22.5"	700c	57.2	73.0°	19.0	72.5°	58.5		28.5	44.5	4.5	6.3	106.3	64.0		
		25"	25"	700c	63.5	72.0°	22.0	72.5°	60.3		28.5	44.5	4.5	6.3	106.3	64.0	
DS Series	15.5"	15.5"	700c	36.6	74.5°	11.4	70.0°	57.5		29.4	45.5	3.8	8.5	109.1	73.8		
	17.5"	17.5"	700c	41.7	74.0°	12.4	71.0°	59.0		29.4	45.5	3.8	8.2	109.5	76.1		
	19"	19"	700c	46.7	73.5°	13.4	71.0°	60.5		29.4	45.5	3.8	8.2	110.5	79.1		
	21"	21"	700c	50.5	73.0°	14.4	71.5°	62.0		29.4	45.5	3.8	7.8	111.0	81.5		
	22.5"	22.5"	700c	54.3	72.5°	15.4	72.0°	63.5		29.4	45.5	3.8	7.5	111.2	84.1		
		25"	25"	700c	63.5	72.0°	22.0	72.5°	60.3		28.5	44.5	4.5	6.3	106.3	64.0	
Neko	14"	14"	700c	33.8	74.5°	11.4	70.0°	55.0		29.4	45.5	3.8	8.9	107.0	69.4		
	16"	16"	700c	38.2	74.0°	11.4	70.5°	56.0		29.4	45.5	3.8	8.5	107.0	71.6		
	18"	18"	700c	43.3	73.5°	12.4	71.0°	57.5		29.4	45.5	3.8	8.2	107.5	74.5		
	14" Stagger	14"	700c	35.6	74.5°	13.4	70.0°	55.0		29.4	45.5	3.8	8.9	107.0	62.2		
	16" Stagger	16"	700c	38.2	74.0°	13.4	70.5°	56.0		29.4	45.5	3.8	8.5	107.0	62.2		
	18" Stagger	18"	700c	43.3	73.5°	14.4	71.0°	57.5		29.4	45.5	3.8	8.2	107.6	62.2		
Chelsea	49cm Stagger	49cm	700c	49.0	74.6°	11.4	70.7°	53.3		27.7	43.5	4.5	7.5	102.5	64.6		
	53cm Stagger	53cm	700c	53.0	73.8°	13.3	71.2°	55.3		27.7	43.5	4.5	7.2	103.3	64.3		
	56cm Stagger	56cm	700c	56.0	73.0°	15.5	72.0°	57.3		27.7	43.5	4.5	6.7	103.5	64.3		
Steel District District	50cm	50cm	700c	50.0	74.5°	11.8	71.0°	53.7		27.9	43.5	4.5	7.5	102.7	75.8		
	54cm	54cm	700c	54.0	73.5°	13.8	71.5°	56.0		27.9	43.5	4.5	7.0	103.4	79.3		
	56cm	56cm	700c	56.0	73.0°	15.5	72.0°	57.3		28.1	43.5	4.5	6.7	103.8	81.5		
	58cm	58cm	700c	58.0	73.0°	16.8	72.5°	58.0		28.1	43.5	4.5	6.4	104.1	83.5		
	61cm	61cm	700c	61.0	72.5°	18.8	72.5°	59.8		28.1	43.5	4.5	6.4	105.3	86.2		
		25"	25"	700c	63.5	72.0°	20.0	72.5°	59.2		28.4	44.5	4.5	6.3	105.3	85.9	
Lync	15"	15"	700c	38.1	74.5°	12.5	70.5°	54.7		28.4	44.5	4.5	7.6	105.5	70.0		
	17.5"	17.5"	700c	44.4	74.0°	14.0	70.5°	54.8		28.4	44.5	4.5	7.6	105.2	74.1		
	20"	20"	700c	50.8	73.5°	16.0	71.5°	56.5		28.4	44.5	4.5	6.9	105.3	78.5		
	22.5"	22.5"	700c	57.2	73.0°	18.0	72.5°	58.1		28.4	44.5	4.5	6.3	105.4	81.6		
	25"	25"	700c	63.5	72.0°	20.0	72.5°	59.2		28.4	44.5	4.5	6.3	105.3	85.9		
Earl	49cm	49cm	700c		74.0°	7.5	72.5°	55.0		28.1	43.0	4.5	6.2	101.7	68.7		
	54cm	54cm	700c		74.0°	7.5	72.5°	57.0		28.1	43.0	4.5	6.2	103.7	73.0		
	57cm	57cm	700c		73.0°	10.5	72.5°	59.0		28.1	43.0	4.5	6.2	104.7	77.0		
	61cm	61cm	700c		73.0°	14.5	72.5°	62.0		28.1	43.0	4.5	6.2	107.7	82.1		
		25"	25"	700c		72.0°		71.0°	61.1		28.4	45.0	4.5	7.2	109.5	76.9	
Dublin (US version)	50cm	50cm	700c		72.5°		70.5°	59.5		28.4	45.0	4.5	7.2	109.0	72.3		
	55cm	55cm	700c		72.0°		71.0°	61.1		28.4	45.0	4.5	7.2	109.5	76.9		
	60cm	60cm	700c		72.0°		71.0°	62.6		28.4	45.0	4.5	7.2	111.0	81.7		

## 2015 Geometry - City

Models	Size	Actual Frame Size	Wheel size	Seat tube	Seat tube angle	Head tube length	Head angle	Effective top tube	Bottom bracket drop	Bottom bracket height	Chainstay length	Offset	Trail	Wheelbase	Standover	Frame reach	Frame stack
CrossRip	49cm	49cm	700c	50.0	74.5°	10.5	70.6°	52.5	7.4	27.7	43.5	4.5	7.6	101.5	73.1	37.6	53.6
	52cm	52cm	700c	52.0	74.0°	12.8	71.2°	54.8	7.4	27.7	43.5	4.5	7.2	102.9	75.3	38.7	56.0
	54cm	54cm	700c	54.0	73.5°	15.0	71.5°	56.9	7.4	27.7	43.5	4.5	7.0	104.2	76.7	39.6	58.2
	56cm	56cm	700c	56.0	73.0°	16.7	72.0°	58.4	7.0	28.1	43.5	4.5	6.7	105.0	78.7	40.2	59.6
	58cm	58cm	700c	58.0	73.0°	18.0	72.5°	59.3	7.0	28.1	43.5	4.5	6.4	105.3	80.1	40.6	61.1
	61cm	61cm	700c	61.0	72.5°	20.0	72.5°	60.9	7.0	28.1	43.5	4.5	6.4	106.3	82.6	41.0	63.0
520 Disc 520	48cm	48cm	700c	44.0	74.3°	11.5	69.5°	52.0	7.5	27.4	45.0	5.2	7.4	104.1	71.3	36.8	54.0
	51cm	51cm	700c	48.2	74.0°	12.5	70.0°	53.1	7.5	27.4	45.0	5.2	7.1	104.5	74.1	37.3	55.1
	54cm	54cm	700c	51.2	73.8°	14.0	71.0°	54.3	7.0	27.8	45.0	5.2	6.5	104.8	76.8	37.8	56.5
	57cm	700c	54.3	73.5°	16.0	71.8°	55.7	7.0	27.8	45.0	5.2	5.9	105.2	79.4	38.3	58.7	
	60cm	60cm	700c	57.5	73.0°	20.0	71.8°	58.3	7.0	27.8	45.0	5.2	5.9	107.4	82.6	39.2	62.5
	63cm	63cm	700c	60.5	72.8°	23.0	72.3°	60.3	7.0	27.8	45.0	5.2	5.6	108.6	85.4	40.0	65.5
720 Disc	49cm	700c	46.6	74.2°	9.6	70.8°	52.6	7.4	27.4	42.6	4.5	7.4	100.2	73.3	37.5	53.3	
	52cm	700c	48.6	74.0°	11.0	71.4°	53.8	7.4	27.4	42.6	4.5	7.0	100.7	75.0	38.0	54.9	
	54cm	700c	50.6	73.7°	12.8	71.8°	55.0	7.2	27.6	42.6	4.5	6.7	101.4	77.0	38.5	56.5	
	56cm	700c	52.6	73.5°	14.5	72.2°	56.3	7.2	27.6	42.6	4.5	6.5	102.1	78.6	39.0	58.2	
	58cm	700c	54.6	73.3°	16.4	72.5°	57.5	7.0	27.8	42.6	4.5	6.3	102.9	80.5	39.5	60.0	
	61cm	700c	56.6	73.0°	19.0	72.8°	59.3	7.0	27.8	42.6	4.5	6.0	104.1	82.5	40.2	62.5	
920 Disc	49cm	49cm	29"	44.0	74.5°	9.5	70.0°	54.0	8.5	28.3	46.5	5.5	7.5	107.2	72.2	38.5	55.6
	52cm	52cm	29"	47.0	74.0°	10.5	70.5°	55.1	8.5	28.3	46.5	5.5	7.2	107.4	74.3	38.8	56.7
	54cm	29"	49.0	73.8°	12.0	41.0°	56.2	8.5	28.3	46.5	5.5	6.8	107.9	76.0	39.2	58.3	
	56cm	56cm	29"	51.0	73.3°	14.5	71.3°	57.8	8.5	28.3	46.5	5.5	6.7	108.8	77.8	39.5	60.8
	58cm	29"	53.0	73.0°	16.5	71.3°	59.4	8.5	28.3	46.5	5.5	6.7	110.0	79.6	40.2	62.7	
	61cm	61cm	29"	56.0	72.8°	18.0	71.5°	60.4	8.5	28.3	46.5	5.5	6.5	110.7	81.7	40.5	64.2
Alliant	15"	15"	700c	38.1	74.5°	11.5	70.5°	54.4		28.5	44.5	5.0	7.1	105.6	69.7		
	17.5"	17.5"	700c	44.4	74.0°	13.0	70.5°	54.8		28.5	44.5	5.0	7.1	105.6	73.8		
	20"	20"	700c	50.8	73.5°	16.0	71.5°	56.8		28.5	44.5	4.5	7.0	105.7	78.6		
	22.5"	22.5"	700c	57.1	73.0°	19.0	72.5°	59.0		28.5	44.5	4.5	6.3	106.3	83.4		
Alliant WSD	15" Stagger	15"	700c	38.1	74.5°	13.0	70.5°	54.3		28.5	44.5	5.0	7.1	105.6	62.7		
	17.5" Stagger	17.5"	700c	44.5	74.0°	15.0	70.5°	54.8		28.5	44.5	5.0	7.1	105.7	63.2		
	20" Stagger	20"	700c	50.8	73.5°	17.0	71.5°	56.8		28.5	44.5	4.5	7.0	105.7	63.6		
Shift	14.5"	14.5"	26"		65.5°	13.7	69.0°	59.4		28.2	49.5	5.0	7.4	108.0	67.0		
	16.5"	16.5"	26"		65.5°	17.2	69.0°	61.1		28.2	49.5	5.0	7.4	109.5	70.6		
	18.5"	18.5"	26"		65.5°	17.2	69.0°	62.0		28.2	49.5	5.0	7.4	110.3	72.7		
	21"	21"	26"		65.5°	22.2	69.0°	64.9		28.2	49.5	5.0	7.4	113.0	76.8		
Shift WSD	13.5" Step-through	13.5"	26"		65.5°	16.2	69.0°	59.1		28.2	49.5	5.0	7.4	107.5	50.3		
	16.5" Step-through	16.5"	26"		65.5°	17.2	69.0°	61.1		28.2	49.5	5.0	7.4	109.5	50.3		
	19" Step-through	19"	26"		65.5°	19.7	69.0°	63.3		28.2	49.5	5.0	7.4	111.5	50.3		
Verve	15"	15"	700c		73.0°	10.0	70.5°	57.2		28.5	46.5	5.1	7.0	109.0	71.5		
	17.5"	17.5"	700c		72.5°	11.5	70.5°	57.8		28.5	46.5	5.1	7.0	109.2	75.3		
	20"	20"	700c		72.0°	12.5	70.5°	59.4		28.5	46.5	5.1	7.0	110.3	78.9		
	22.5"	22.5"	700c		71.5°	15.5	71.0°	61.3		28.5	46.5	5.1	6.6	111.1	83.5		
	25"	25"	700c		71.5°	20.5	71.0°	62.0		28.5	46.5	5.1	6.6	111.8	89.0		
Verve WSD	13" Step-through	13"	700c		73.0°	17.0	70.5°	56.0		28.5	46.5	5.1	6.9	108.3	44.8		
	16" Step-through	16"	700c		72.5°	18.0	70.5°	57.5		28.5	46.5	5.1	7.0	109.2	44.8		
	19" Step-through	19"	700c		72.0°	18.0	70.5°	60.0		28.5	46.5	5.1	7.0	111.0	44.8		
Pure	16"	16"	26"		68.0°	23.5	69.0°	68.5		28.5	60.0	5.0	7.4	117.5	72.6		
Pure S	14" Step-through	14"	26"		68.0°	23.5	69.0°	68.5		28.5	60.0	5.0	7.4	117.5	51.3		
T 900	18.5" Front	18.5"	26"		72.5°	19.5	73.0°	57.7		28.7	43.5	5.5	4.4	177.1	76.1		
	14.5" Rear	14.5"	26"		72.5°			22.7		28.6					55.9		
T80+ (US version)	50cm	50cm	700c	50.0	73.0°	16.0	70.5°	58.3		30.2	45.5	4.5	8.1	109.0	80.0		
	55cm	55cm	700c	55.0	73.0°	16.0	70.5°	59.3		30.2	45.5	4.5	8.1	110.0	82.8		
	60cm	60cm	700c	60.0	73.0°	18.0	70.5°	60.7		30.2	45.5	4.5	8.1	111.5	86.4		
	50cm Lowstep	50cm	700c	45.0	73.0°	16.0	70.5°	56.4		28.9	46.5	4.5	8.1	109.3	57.4		
	55cm Lowstep	55cm	700c	50.0	73.0°	18.0	70.5°	59.6		28.9	46.5	4.5	8.1	110.8	54.9		