

## 2015 Geometry - Mountain

Models	Size	Actual Frame Size	Wheel size	Seat tube	Seat tube angle	Effective seat tube angle	Head tube length	Head angle	Effective top tube	Bottom bracket drop	Bottom bracket height	Chainstay length	Offset	Trail	Wheelbase	Standover	Frame reach	Frame stack
Fuel EX 29	15.5"	15.5"	29"	39.4	73.6°		10.5	69.5°	56.7	3.2	33.8	45.2	5.1	8.4	110.8	77.9	39.0	60.1
	17.5"	16.5"	29"	42.0	73.6°		10.5	69.5°	59.8	3.2	33.8	45.2	5.1	8.4	113.9	76.5	42.1	60.1
	18.5"	17.5"	29"	44.5	73.6°		11.5	69.5°	61.2	3.2	33.8	45.2	5.1	8.4	115.4	77.3	43.2	61.1
	19.5"	18.5"	29"	47.0	73.6°		11.5	69.5°	62.7	3.2	33.8	45.2	5.1	8.4	116.9	76.8	44.7	61.1
	21.5"	20.5"	29"	50.8	73.6°		13.0	69.5°	65.0	3.2	33.8	45.2	5.1	8.4	119.3	77.0	46.6	62.5
Fuel EX 27.5	23"	22"	29"	55.9	73.6°		14.5	69.5°	66.3	3.2	33.8	45.2	5.1	8.4	120.7	78.8	47.5	63.9
	15.5"	15.5"	27.5"	36.8	73.0°		9.5	68.0°	55.5	1.7	33.3	43.3	4.4	8.4	110.1	74.0	37.4	56.0
	17.5"	16.5"	27.5"	41.9	73.0°		10.0	68.0°	58.8	1.7	33.3	43.3	4.4	8.4	113.7	73.0	41.5	65.5
	18.5"	17.5"	27.5"	44.5	73.0°		11.0	68.0°	60.8	1.7	33.3	43.3	4.4	8.4	115.5	73.0	43.2	57.4
	19.5"	18.5"	27.5"	47.0	73.0°		12.0	68.0°	62.7	1.7	33.3	43.3	4.4	8.4	117.0	74.0	44.9	58.3
Lush Carbon	21.5"	20.5"	27.5"	52.1	73.0°		14.0	68.0°	65.3	1.7	33.3	43.3	4.4	8.4	119.4	74.2	46.9	60.2
	14"	14"	27.5"	35.5	74.0°		9.5	68.0°	53.0	1.5	33.5	43.3	4.4	9.4	107.0	69.1	37.0	55.9
	15.5"	15.5"	27.5"	39.4	74.0°		9.5	68.0°	55.0	1.5	33.5	43.3	4.4	9.4	109.0	68.8	39.0	55.9
	17"	16"	27.5"	40.6	74.0°		10.5	68.0°	58.0	1.5	33.5	43.3	4.4	9.4	112.1	68.7	41.7	56.8
	18.5"	17.5"	27.5"	44.5	74.0°		12.0	68.0°	60.5	1.5	33.5	43.3	4.4	9.4	114.7	69.0	43.8	58.2
Lush Alloy	14"	14"	27.5"	35.5	74.0°		9.5	68.0°	53.0	1.5	33.5	43.3	4.4	9.4	107.0	69.1	37.0	55.9
	15.5"	15.5"	27.5"	39.4	74.0°		9.5	68.0°	55.0	1.5	33.5	43.3	4.4	9.4	109.0	68.2	39.0	55.9
	17"	16"	27.5"	40.6	74.0°		10.5	68.0°	58.0	1.5	33.5	43.3	4.4	9.4	112.1	68.7	41.7	56.8
	18.5"	17.5"	27.5"	44.5	74.0°		12.0	68.0°	60.5	1.5	33.5	43.3	4.4	9.4	114.7	68.8	43.8	58.2
	18.5"	17.5"	27.5"	44.5	74.0°		12.0	68.0°	60.5	1.5	33.5	43.3	4.4	9.4	114.7	69.0	43.8	58.2
Stache	15.5"	15.5"	29"	36.8	73.0°		10.3	68.3°	56.8		31.6	44.5	5.1	9.2	110.2	76.0	38.8	61.0
	17.5"	16.5"	29"	41.9	72.5°		10.3	68.3°	60.0		31.6	44.5	5.1	9.2	112.8	77.7	41.4	61.0
	19"	18"	29"	45.7	72.0°		10.3	68.6°	62.0		31.6	44.5	5.1	9.0	113.9	79.4	42.7	61.1
	21"	20"	29"	50.8	72.0°		11.8	68.6°	64.0		31.6	44.5	5.1	9.0	116.1	82.4	44.3	62.5
	23"	22"	29"	54.5	72.0°		11.8	68.6°	66.1		31.6	44.5	5.1	9.0	118.1	84.4	46.4	62.5
Farley	14.5"	14.5"	26"	34.3	73.0°		10.0	70.0°	55.4	5.5	31.3	44.0	4.6	8.5	105.1	75.7	37.2	59.5
	15.5"	15.5"	26"	36.8	73.0°		10.0	70.0°	56.6	5.5	31.3	44.0	4.6	8.5	106.3	77.0	38.4	59.5
	17.5"	16.5"	26"	41.9	73.0°		10.0	70.0°	59.3	5.5	31.3	44.0	4.6	8.5	109.0	78.2	41.1	59.5
	19.5"	18.5"	26"	47.0	73.0°		12.0	70.0°	63.0	5.5	31.3	44.0	4.6	8.5	112.8	81.7	44.2	61.3
	21.5"	20.5"	26"	52.1	73.0°		12.0	70.0°	64.3	5.5	31.3	44.0	4.6	8.5	114.1	83.2	45.5	61.3
Remedy Carbon 27.5 <i>Low geometry</i>	15.5"	15.5"	27.5"	39.4	67.5°		10.0	67.5°	54.9	1.5	33.8	43.5	4.3	10.0	109.8	77.2	36.6	59.3
	17.5"	16.5"	27.5"	41.9	67.5°		10.0	67.5°	58.2	1.5	33.8	43.5	4.3	10.0	113.1	75.8	39.4	69.4
	18.5"	17.5"	27.5"	44.5	67.5°		10.5	67.5°	60.1	1.5	33.8	43.5	4.3	10.0	115.1	74.4	41.7	69.9
	19.5"	18.5"	27.5"	47.0	67.5°		11.0	67.5°	61.8	1.5	33.8	43.5	4.3	10.0	116.7	74.2	43.2	60.4
	21.5"	20.5"	27.5"	50.8	67.5°		12.5	67.5°	64.6	1.5	33.8	43.5	4.3	10.0	119.6	73.9	45.5	61.8
Remedy Carbon 27.5 <i>High geometry</i>	15.5"	15.5"	27.5"	39.4	68.2°		10.0	68.2°	54.6	0.7	34.6	43.3	4.3	9.5	109.7	77.9	37.3	58.9
	17.5"	16.5"	27.5"	41.9	68.2°		10.0	68.2°	57.9	0.7	34.6	43.3	4.3	9.5	113.0	76.5	40.6	58.9
	18.5"	17.5"	27.5"	44.5	68.1°		10.5	68.1°	59.8	0.7	34.6	43.3	4.3	9.5	114.9	75.1	42.4	59.4
	19.5"	18.5"	27.5"	47.0	68.1°		11.0	68.1°	61.5	0.7	34.6	43.3	4.3	9.5	116.6	74.9	43.9	59.9
	21.5"	20.5"	27.5"	50.8	68.1°		12.5	68.1°	64.3	0.7	34.6	43.3	4.3	9.5	119.3	74.6	46.1	61.3
Remedy AL 27.5 <i>Low geometry</i>	15.5"	15.5"	27.5"	39.4	67.5°		10.0	67.5°	54.9	1.5	33.8	43.5	4.3	10.0	109.8	77.6	36.6	59.3
	17.5"	16.5"	27.5"	41.9	67.5°		10.0	67.5°	58.2	1.5	33.8	43.5	4.3	10.0	113.1	75.8	39.4	69.4
	18.5"	17.5"	27.5"	44.5	67.5°		10.5	67.5°	60.1	1.5	33.8	43.5	4.3	10.0	115.1	74.4	41.7	69.9
	19.5"	18.5"	27.5"	47.0	67.5°		11.0	67.5°	61.8	1.5	33.8	43.5	4.3	10.0	116.7	74.0	43.2	60.4
	21.5"	20.5"	27.5"	50.8	67.5°		12.5	67.5°	64.6	1.5	33.8	43.5	4.3	10.0	119.6	74.5	45.5	61.8
Remedy AL 27.5 <i>High geometry</i>	15.5"	15.5"	27.5"	39.4	68.2°		10.0	68.2°	54.6	0.7	34.6	43.3	4.3	9.5	109.7	78.2	37.3	58.9
	17.5"	16.5"	27.5"	41.9	68.2°		10.0	68.2°	57.9	0.7	34.6	43.3	4.3	9.5	113.0	76.5	40.6	58.9
	18.5"	17.5"	27.5"	44.5	68.1°		10.5	68.1°	59.8	0.7	34.6	43.3	4.3	9.5	114.9	75.1	42.4	59.4
	19.5"	18.5"	27.5"	47.0	68.1°		11.0	68.1°	61.5	0.7	34.6	43.3	4.3	9.5	116.6	74.7	43.9	59.9
	21.5"	20.5"	27.5"	50.8	68.1°		12.5	68.1°	64.3	0.7	34.6	43.3	4.3	9.5	119.3	75.3	46.1	61.3
Remedy Carbon 29 <i>Low geometry</i>	15.5"	15.5"	29"	39.4	68.0°		10.0	67.5°	54.6	2.0	35.0	44.5	5.1	9.8	112.8	77.1	38.6	60.5
	17.5"	16.5"	29"	41.9	68.0°		10.0	67.5°	57.6	2.0	35.0	44.5	5.1	9.8	115.8	76.7	41.6	60.5
	18.5"	17.5"	29"	44.5	68.0°		10.5	67.5°	59.4	2.0	35.0	44.5	5.1	9.8	117.5	74.5	43.2	60.9
	19.5"	18.5"	29"	47.0	68.0°		11.0	67.5°	60.9	2.0	35.0	44.5	5.1	9.8	119.0	75.1	44.7	60.9
	21.5"	20.5"	29"	52.1	68.0°		12.5	67.5°	63.1	2.0	35.0	44.5	5.1	9.8	121.2	76.6	46.5	61.9
Remedy Carbon 29 <i>High geometry</i>	15.5"	14.5"	29"	39.4	69.0°		10.0	68.2°	54.4	2.0	35.9	44.3	5.1	9.3	112.6	77.9	39.3	60.0
	17.5"	16.5"	29"	41.9	69.0°		10.0	68.2°	57.3	2.0	35.9	44.3	5.1	9.3	115.6	77.5	42.3	60.0
	18.5"	17.5"	29"	44.5	69.0°		10.5	68.2°	59.1	2.0	35.9	44.3	5.1	9.3	117.4	75.3	43.9	60.4
	19.5"	20.5"	29"	47.0	69.0°		11.0	68.2°	60.6	2.0	35.9	44.3	5.1	9.3	118.9	75.9	45.4	60.4
	21.5"	22"	29"	52.1	69.0°		12.5	68.2°	62.8	2.0	35.9	44.3	5.1	9.3	121.1	77.5	47.2	61.3
Remedy AL 29 <i>Low geometry</i>	15.5"	15.5"	29"	39.4	68.0°		10.0	67.5°	54.6	2.0	35.0	44.5	5.1	9.8	112.8	77.9	38.5	60.6
	17.5"	16.5"	29"	41.9	68.0°		10.0	67.5°	57.6	2.0	35.0	44.5	5.1	9.8	115.8	76.5	41.5	60.6
	19"	18"	29"	45.7	68.0°		10.5	67.5°	59.7	2.0	35.0	44.5	5.1	9.8	117.9	76.8	43.4	61.1
	21"	20"	29"	50.8	68.0°		11.0	67.5°	61.8	2.0	35.0	44.5	5.1	9.8	120.0	78.1	45.1	62.0
	23"	22"	29"	55.9	68.0°		12.5	67.5°	63.9	2.0	35.0	44.5	5.1	9.8	122.1	81.8	46.9	62.9
Remedy AL 29 <i>High geometry</i>	15.5"	15.5"	29"	39.4	69.0°		10.0	68.2°	54.4	2.0	35.9	44.3	5.1	9.3	112.7			

## 2015 Geometry - Mountain

Models	Size	Actual Frame Size	Wheel size	Seat tube	Seat tube angle	Effective seat tube angle	Head tube length	Head angle	Effective top tube	Bottom bracket drop	Bottom bracket height	Chainstay length	Offset	Trail	Wheelbase	Standover	Frame reach	Frame stack
Slash <i>Low geometry</i>	15.5"	15.5"	27.5"	39.4	66.5°		10.0	65.0°	55.7	0.6	35.0	43.5	4.4	11.7	114.9	79.5	39.7	58.1
	17.5"	16.5"	27.5"	41.9	66.5°		10.0	65.0°	58.7	0.6	35.0	43.5	4.4	11.7	117.9	77.7	42.7	58.1
	18.5"	17.5"	27.5"	44.5	66.5°		10.0	65.0°	60.0	0.6	35.0	43.5	4.4	11.7	119.2	76.2	44.0	58.1
	19.5"	18.5"	27.5"	47.0	66.5°		11.0	65.0°	61.4	0.6	35.0	43.5	4.4	11.7	120.5	75.6	45.0	59.0
	21.5"	20.5"	27.5"	52.1	66.5°		12.0	65.0°	64.2	0.6	35.0	43.5	4.4	11.7	123.4	74.5	47.4	59.9
Slash <i>High geometry</i>	15.5"	15.5"	27.5"	39.4	67.2°		10.0	65.7°	55.5	-0.2	35.8	43.3	4.4	11.7	114.7	80.2	40.4	57.6
	17.5"	16.5"	27.5"	41.9	67.1°		10.0	65.6°	58.5	-0.2	35.8	43.3	4.4	11.7	117.7	78.4	43.4	57.6
	18.5"	17.5"	27.5"	44.5	67.1°		10.0	65.6°	59.8	-0.2	35.8	43.3	4.4	11.7	119.0	76.9	44.7	57.6
	19.5"	18.5"	27.5"	47.0	67.1°		11.0	65.6°	61.1	-0.3	35.9	43.3	4.4	11.7	120.4	76.4	45.6	58.5
	21.5"	20.5"	27.5"	52.1	67.1°		12.0	65.6°	64.5	-0.3	35.9	43.3	4.4	11.7	123.2	75.3	48.0	59.4
Session DH <i>Low geometry</i>	S	S	27.5"	39.0	57.0°		11.5	63.6°	47.7	1.0	35.6	44.5	5.2	118.0	118.3	80.4	38.2	60.7
	M	M	27.5"	39.0	57.0°		11.5	63.6°	51.5	1.0	35.6	44.5	5.2	118.0	120.3	79.0	40.2	60.7
	L	L	27.5"	39.0	57.0°		11.5	63.6°	53.9	1.0	35.6	44.5	5.2	118.0	122.7	78.4	42.6	60.7
	XL	XL	27.5"	39.0	57.0°		11.5	63.6°	58.4	1.0	35.6	44.5	5.2	118.0	125.1	76.7	45.0	60.7
Session DH <i>High geometry</i>	S	S	27.5"	39.0	57.6°		11.5	64.2°	57.0	1.4	36.4	44.3	5.2	114.4	118.5	81.0	38.9	60.3
	M	M	27.5"	39.0	57.6°		11.5	64.2°	59.0	1.4	36.4	44.3	5.2	114.4	120.5	79.3	40.8	60.3
	L	L	27.5"	39.0	57.6°		11.5	64.2°	61.4	1.4	36.4	44.3	5.2	114.4	122.9	79.0	43.2	60.3
	XL	XL	27.5"	39.0	57.6°		11.5	64.2°	63.8	1.4	36.4	44.3	5.2	114.4	125.3	77.5	45.6	60.3
Session Park <i>Low geometry</i>	M	M	26"	4.4	57.0°		12.5	63.6°	58.6	1.3	35.6	42.0	4.5	12.0	116.3	74.7	39.2	59.3
	L	L	26"	4.4	57.0°		12.5	63.6°	61.0	1.3	35.6	42.0	4.5	12.0	118.8	74.7	41.7	59.3
Session Park <i>High geometry</i>	M	M	26"	4.4	57.6°		12.5	64.2°	58.2	2.1	36.4	41.8	4.5	11.9	116.0	75.4	39.8	58.8
	L	L	26"	4.4	57.6°		12.5	64.2°	60.7	2.1	36.4	41.8	4.5	12.0	118.0	75.4	42.3	58.9
Ticket S <i>Low geometry</i>	L	Long	26"	33.1	75.0°	72.5°	12.3	68.5°	56.5	0.3	33.0	40.0	4.0	8.8	108.5	37.5	42.6	55.3
Ticket S <i>High geometry</i>	L	Long	26"	33.1	75.8°	73.3°	12.3	69.3°	56.3	0.6	33.9	39.8	4.0	8.8	108.3	38.3	43.3	54.7
Ticket Hardtail	L	Long	26"	33.0	71.0°		12.0	70.0°	57.0	1.2	32.0	39.8	4.0	7.7	105.0	69.1	41.4	54.3
Superfly FS	15.5"	15.5"	29"	39.4	73.8°	70.0°	10.5	70.0°	55.6	3.9	33.0	45.2	5.1	8.0	109.9	78.0	39.2	59.3
	17.5"	16.5"	29"	44.5	73.8°	70.0°	11.5	70.0°	58.8	3.9	33.0	45.2	5.1	8.0	113.1	77.1	42.1	60.3
	19"	18"	29"	48.3	73.8°	70.0°	12.5	70.0°	60.6	3.9	33.0	45.2	5.1	8.0	114.9	76.3	43.6	61.2
	21"	20"	29"	53.3	73.8°	70.0°	13.5	70.0°	62.8	3.9	33.0	45.2	5.1	8.0	117.1	77.7	45.4	62.1
	23"	22"	29"	58.4	73.8°	70.0°	14.5	70.0°	64.8	3.9	33.0	45.2	5.1	8.0	119.0	79.0	47.0	63.1
Superfly FS AL	15.5"	15.5"	29"	39.4	70.0°		10.5	70.0°	55.8	3.9	33.0	45.2	5.1	8.0	109.9	78.9	39.2	59.3
	17.5"	16.5"	29"	41.9	70.0°		11.5	70.0°	58.9	3.9	33.0	45.2	5.1	8.0	113.1	78.4	42.1	60.3
	18.5"	17.5"	29"	44.5	70.0°		11.5	70.0°	60.1	3.9	33.0	45.2	5.1	8.0	114.3	77.8	43.3	60.3
	19.5"	18.5"	29"	47.0	70.0°		11.5	70.0°	61.2	3.9	33.0	45.2	5.1	8.0	115.4	77.2	44.4	60.3
	21.5"	20.5"	29"	52.1	70.0°		13.0	70.0°	63.7	3.9	33.0	45.2	5.1	8.0	117.9	76.4	46.4	61.7
23"	22"	29"	55.9	70.0°		14.0	70.0°	64.9	3.9	33.0	45.2	5.1	8.0	119.2	78.5	47.4	62.6	
Superfly Carbon SL	15.5"	15.5"	29"	36.8	73.0°		10.3	69.3°	57.0	5.3	31.6	44.5	5.1	8.5	109.0	74.8	38.6	60.2
	17.5"	16.5"	29"	41.6	72.5°		10.3	69.3°	60.2	5.3	31.6	44.5	5.1	8.5	111.6	76.9	41.2	60.2
	19"	18"	29"	45.7	72.0°		10.3	69.6°	62.2	5.3	31.6	44.5	5.1	8.3	112.7	78.9	42.6	60.3
	21"	20"	29"	50.8	72.0°		11.8	69.6°	64.3	5.3	31.6	44.5	5.1	8.3	114.8	82.2	44.2	61.7
	23"	22"	29"	54.5	72.0°		11.8	69.6°	66.3	5.3	31.6	44.5	5.1	8.3	116.9	84.4	46.2	61.7
Superfly Carbon	15.5"	15.5"	27.5"	36.8	73.0°		10.0	69.3°	55.8	4.8	30.2	42.5	4.4	8.5	105.3	72.1	37.2	58.3
	17.5"	16.5"	29"	41.9	72.5°		10.0	69.3°	60.2	5.8	31.1	43.5	5.1	8.5	110.3	76.7	41.2	60.0
	18.5"	17.5"	29"	44.4	72.3°		10.0	69.6°	62.0	5.8	31.1	43.5	5.1	8.3	111.6	77.9	42.7	60.1
	19.5"	18.5"	29"	47.0	72.0°		10.0	69.6°	63.9	5.8	31.1	43.5	5.1	8.3	113.1	79.2	44.3	60.1
	21.5"	20.5"	29"	52.1	72.0°		12.0	69.6°	65.9	5.8	31.1	43.5	5.1	8.3	115.2	82.9	45.7	61.9
23"	22"	29"	55.9	72.0°		12.0	69.6°	67.3	5.8	31.1	43.5	5.1	8.3	116.6	84.7	47.1	61.9	
Superfly AL	15.5"	15.5"	27.5"	36.8	73.0°		10.0	69.3°	55.8	4.8	30.2	42.5	4.4	8.5	105.3	72.1	37.2	58.3
	17.5"	16.5"	29"	41.9	72.5°		10.0	69.3°	60.2	5.8	31.1	43.5	5.1	8.5	110.3	76.5	41.2	60.0
	18.5"	17.5"	29"	44.4	72.3°		10.0	69.6°	62.0	5.8	31.1	43.5	5.1	8.3	111.6	77.6	42.7	60.1
	19.5"	18.5"	29"	47.0	72.0°		10.0	69.6°	63.9	5.8	31.1	43.5	5.1	8.3	113.1	79.5	44.3	60.1
	21.5"	20.5"	29"	52.1	72.0°		12.0	69.6°	65.9	5.8	31.1	43.5	5.1	8.3	115.2	82.3	45.7	61.9
23"	22"	29"	55.9	72.0°		12.0	69.6°	67.3	5.8	31.1	43.5	5.1	8.3	116.6	84.4	47.1	61.9	
Superfly AL SS	15.5"	15.5"	29"	36.8	73.0°		10.0	69.3°	57.0	5.8	31.1	43.5	5.1	8.5	107.7	74.7	38.6	60.0
	17.5"	16.5"	29"	41.9	72.5°		10.0	69.3°	60.2	5.8	31.1	43.5	5.1	8.5	110.3	76.5	41.2	60.0
	18.5"	17.5"	29"	44.4	72.3°		10.0	69.6°	62.0	5.8	31.1	43.5	5.1	8.3	111.6	77.6	42.7	60.1
	19.5"	18.5"	29"	47.0	72.0°		10.0	69.6°	63.9	5.8	31.1	43.5	5.1	8.3	113.1	79.5	44.3	60.1
	21.5"	20.5"	29"	52.1	72.0°		12.0	69.6°	65.9	5.8	31.1	43.5	5.1	8.3	115.2	82.3	45.7	61.9
23"	22"	29"	55.9	72.0°		12.0	69.6°	67.3	5.8	31.1	43.5	5.1	8.3	116.6	84.4	47.1	61.9	

## 2015 Geometry - Mountain

Models	Size	Actual Frame Size	Wheel size	Seat tube	Seat tube angle	Effective seat tube angle	Head tube length	Head angle	Effective top tube	Bottom bracket drop	Bottom bracket height	Chainstay length	Offset	Trail	Wheelbase	Standover	Frame reach	Frame stack
Call Carbon	13.5"	13.5"	27.5"	34.3	73.0°		10.0	69.0°	54.1	4.8	30.2	42.5	4.4	8.7	103.7	71.0	37.0	56.3
	15.5"	15.5"	27.5"	36.8	73.0°		10.0	69.3°	55.8	4.8	30.2	42.5	4.4	8.5	105.3	72.1	37.2	58.3
	17.5"	16.5"	29"	41.9	72.5°		10.0	69.3°	60.2	5.8	31.1	43.5	5.1	8.5	110.3	76.7	41.2	60.0
	18.5"	17.5"	29"	44.4	72.3°		10.0	69.6°	62.0	5.8	31.1	43.5	5.1	8.3	111.6	77.9	42.7	60.1
Calli	13.5"	13.5"	27.5"	34.3	73.0°		10.0	69.0°	54.1	4.8	30.2	42.5	4.4	8.7	103.7	71.0	37.0	56.3
	15.5"	15.5"	27.5"	36.8	73.0°		10.0	69.3°	55.8	4.8	30.2	42.5	4.4	8.5	105.3	72.1	37.2	58.3
	17.5"	16.5"	29"	41.9	72.5°		10.0	69.3°	60.2	5.8	31.1	43.5	5.1	8.5	110.3	76.5	41.2	60.0
	18.5"	17.5"	29"	44.4	72.3°		10.0	69.6°	62.0	5.8	31.1	43.5	5.1	8.3	111.6	77.6	42.7	60.1
X-Caliber	13.5"	13.5"	27.5"	34.3	73.0°		10.0	69.0°	52.5	4.8	30.6	43.8	4.4	8.9	103.3	66.0	35.2	56.5
	15.5"	15.5"	27.5"	39.4	73.0°		10.0	69.3°	56.0	4.8	30.6	43.8	4.4	8.7	106.6	74.5	38.1	58.5
	17.5"	16.5"	29"	41.9	72.5°		10.0	69.3°	60.2	5.3	31.6	44.5	5.1	8.5	111.6	76.5	41.3	60.0
	18.5"	17.5"	29"	44.4	72.3°		10.0	69.6°	62.0	5.3	31.6	44.5	5.1	8.3	112.8	77.7	42.8	60.1
	19.5"	18.5"	29"	47.0	72.0°		10.0	69.6°	63.9	5.3	31.6	44.5	5.1	8.3	114.4	78.9	44.4	60.1
	21.5"	20.5"	29"	52.1	72.0°		12.0	69.6°	65.9	5.3	31.6	44.5	5.1	8.3	116.5	82.5	45.8	62.0
	23"	22"	29"	55.9	72.0°		12.0	69.6°	67.3	5.3	31.6	44.5	5.1	8.3	117.9	84.8	47.2	62.0
Marlin	13.5"	13.5"	27.5"	34.3	73.0°		10.0	69.0°	52.5	4.8	30.6	43.8	4.4	8.9	103.3	66.0	35.2	56.5
	15.5"	15.5"	27.5"	39.4	73.0°		10.0	69.3°	56.0	4.8	30.6	43.8	4.4	8.7	106.6	74.5	38.1	58.5
	17.5"	16.5"	29"	41.9	72.5°		10.0	69.3°	60.2	5.3	31.6	44.5	5.1	8.5	111.6	76.5	41.3	60.0
	18.5"	17.5"	29"	44.4	72.3°		10.0	69.6°	62.0	5.3	31.6	44.5	5.1	8.3	112.8	77.7	42.8	60.1
	19.5"	18.5"	29"	47.0	72.0°		10.0	69.6°	63.9	5.3	31.6	44.5	5.1	8.3	114.4	78.9	44.4	60.1
	21.5"	20.5"	29"	52.1	72.0°		12.0	69.6°	65.9	5.3	31.6	44.5	5.1	8.3	116.5	82.5	45.8	62.0
Skye	13.5"	13.5"	27.5"	34.3	73.0°		10.0	69.0°	52.5	4.8	30.6	43.8	4.4	8.9	103.3	66.0	35.2	56.5
	15.5"	15.5"	27.5"	39.4	73.0°		10.0	69.3°	56.0	4.8	30.6	43.8	4.4	8.7	106.6	74.5	38.1	58.5
	17"	16"	29"	40.6	73.0°		10.0	69.0°	59.0		31.2	44.5	5.1	8.5	111.3	66.9	40.7	59.8
	18.5"	17.5"	29"	44.5	73.0°		10.0	69.0°	61.2		31.2	44.5	5.1	8.5	113.5	68.5	42.9	59.8
Skye S	13"	13"	26"	33.0	74.0°		11.0	70.5°	52.4		28.7	43.0	4.0	7.6	101.9	65.5		
	16"	16"	26"	40.6	73.5°		11.0	70.5°	54.6		29.1	43.0	4.0	7.6	103.6	63.1		
Skye 820 WSD	19.5"	19.5"	26"	49.5	73.0°		17.0	70.5°	57.5		29.3	43.0	4.0	7.6	106.4	62.5		
3 Series 820	13"	13"	26"	33.0	74.0°		11.0	70.5°	52.4		28.7	43.0	4.0	7.6	101.9	70.5		
	16"	16"	26"	40.6	73.5°		11.0	70.5°	55.0		29.1	43.0	4.0	7.6	104.0	73.8		
	18"	18"	26"	45.7	73.5°		13.0	70.5°	56.5		29.3	43.0	4.0	7.6	105.7	77.2		
	19.5"	19.5"	26"	49.5	73.0°		15.0	70.5°	58.0		29.3	43.0	4.0	7.6	106.8	79.9		
	21"	21"	26"	53.3	73.0°		17.0	70.5°	59.0		29.3	43.0	4.0	7.6	107.9	82.7		
	22.5"	22.5"	26"	57.2	72.5°		19.0	70.5°	60.0		29.5	43.0	4.0	7.6	108.4	85.7		
Police	15.5"	15.5"	29"	39.4	73.0°		10.3	69.3°	57.0	5.3	31.2	44.5	5.1	8.3	109.0	75.4	38.6	60.2
	17.5"	17.5"	29"	44.5	72.5°		10.3	69.3°	60.2	5.3	31.2	44.5	5.1	8.3	111.6	77.5	41.2	60.2
	19"	19"	29"	48.3	72.0°		10.3	69.6°	62.2	5.3	31.2	44.5	5.1	8.1	112.7	79.5	42.6	60.3
	21"	21"	29"	53.3	72.0°		11.8	69.6°	64.3	5.3	31.2	44.5	5.1	8.1	114.8	82.8	44.2	61.7
	23"	23"	29"	58.4	72.0°		11.8	69.6°	66.3	5.3	31.2	44.5	5.1	8.1	116.9	85.9	46.2	61.7
Powerfly+	15.5"	15.5"	29"	40.0	73.0°		14.0	69.0°	56.1	5.3	33.2	48.5	5.1		112.0	78.8	36.5	63.8
	17.5"	17.5"	29"	42.5	72.5°		14.0	69.0°	58.3	5.3	33.2	48.5	5.1		113.7	79.0	38.2	63.8
	19"	19"	29"	47.0	72.5°		16.0	69.0°	60.7	5.3	33.2	48.5	5.1		116.2	81.1	40.0	65.6
	21"	21"	29"	51.5	72.5°		16.0	69.0°	63.2	5.3	33.2	48.5	5.1		118.7	84.3	42.5	65.6
Powerfly+ WSD	15.5"	15.5"	29"	40.0	73.0°		14.0	69.0°	55.5	4.8	32.0	46.5	4.4		109.5	72.5	36.5	62.1
	17.5"	17.5"	29"	42.5	72.5°		14.0	69.0°	57.8	4.8	32.0	46.5	4.4		111.2	72.0	38.2	62.1
Powerfly+ FS	15.5"	15.5"	29"	36.8	71.0°		13.0	68.0°	55.5	1.7	33.3	47.0	4.4	9.4	110.1	73.0	38.9	59.5
	17.5"	17.5"	29"	41.9	71.0°		13.2	68.0°	58.0	1.7	33.3	47.0	4.4	9.4	112.6	73.0	42.2	59.5
	18.5"	18.5"	29"	44.5	71.0°		14.0	68.0°	60.5	1.7	33.3	47.0	4.4	9.4	115.1	73.0	39.8	60.2
	19.5"	19.5"	29"	47.0	71.0°		14.0	68.0°	62.7	1.7	33.3	47.0	4.4	9.4	117.3	73.0	42.0	60.2
	21.5"	21.5"	29"	52.1	71.0°		16.0	68.0°	65.3	1.7	33.3	47.0	4.4	9.4	120.0	73.0	43.9	62.1