

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
Farley Alloy Rigid Fork	S	15.5"	27.5"	38.0	72.5°	74.0°	9.0	68.5°	56.5	32.0	6.5	45.0	4.2	10.7	109.7	73.0	40.0	58.9
	M	17.5"	27.5"	42.0	72.5°	74.0°	10.0	68.5°	59.8	32.0	6.5	45.0	4.2	10.7	113.1	74.0	43.0	59.9
	L	18.5"	27.5"	45.0	72.5°	74.0°	11.5	68.5°	63.3	32.0	6.5	45.0	4.2	10.7	116.6	76.0	46.0	61.3
	XL	19.5"	27.5"	49.0	72.5°	74.0°	13.0	68.5°	67.2	32.0	6.5	45.0	4.2	10.7	120.7	78.0	49.5	62.6
Farley Alloy Suspension Fork	S	15.5"	27.5"	38.0	71.7°	73.2°	9.0	67.7°	56.8	32.6	5.9	45.0	5.1	10.3	111.3	73.8	39.1	59.5
	M	17.5"	27.5"	42.0	71.7°	73.2°	10.0	67.7°	60.9	32.6	5.9	45.0	5.1	10.3	114.7	74.8	42.1	60.5
	L	18.5"	27.5"	45.0	71.7°	73.2°	11.5	67.7°	63.5	32.6	5.9	45.0	5.1	10.3	118.2	76.8	45.2	61.9
	XL	19.5"	27.5"	49.0	71.7°	73.2°	13.0	67.7°	67.5	32.6	5.9	45.0	5.1	10.3	122.3	78.7	48.7	63.3
Farley Carbon	S	15.5"	27.5"	39.4	71.5°	73.0°	10.0	69.0°	56.7	32.1	6.7	45.5	5.1	9.4	109.2	76.3	38.3	60.1
	M	17.5"	27.5"	41.9	71.5°	73.0°	10.0	69.0°	59.4	32.1	6.7	45.5	5.1	9.4	111.9	75.7	41.0	60.1
	L	19.5"	27.5"	47.0	71.5°	73.0°	12.0	69.0°	63.1	32.1	6.7	45.5	5.1	9.4	115.8	77.6	44.1	61.9
	XL	21.5"	27.5"	52.1	71.5°	73.0°	12.0	69.0°	64.4	32.1	6.7	45.5	5.1	9.4	117.1	77.4	45.4	61.9

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
Marlin Gen 2	XS	13.5"	27.5"	34.3	73.5°	73.5°	9.0	69.3°	54.4	29.2	5.8	43.8	4.2	8.8	104.9	65.8	37.6	56.5
	S	15.5"	27.5"	36.8	73.5°	73.5°	9.0	69.3°	55.5	30.2	4.8	43.8	4.2	8.8	106.6	68.6	38.5	57.4
	M	17.5"	29"	41.9	71.9°	73.0°	9.0	69.5°	60.2	31.0	5.8	43.8	4.2	9.3	110.0	74.8	41.8	60.2
	ML	18.5"	29"	44.4	71.9°	73.0°	9.0	69.5°	61.8	31.0	5.8	43.8	4.2	9.3	111.6	75.8	43.4	60.2
	L	19.5"	29"	47.0	71.9°	73.0°	10.0	69.5°	63.8	31.0	5.8	43.8	4.2	9.3	113.7	75.7	45.1	61.1
	XL	21.5"	29"	52.1	71.9°	73.0°	12.0	69.5°	65.9	31.0	5.8	43.8	4.2	9.3	115.9	76.9	46.6	63.0
	XXL	23"	29"	55.9	71.9°	73.0°	12.0	69.5°	67.3	31.1	5.8	43.8	4.2	9.3	117.3	80.4	48.0	63.0
Marlin Gen 3	XXS	13.5"	26"	32.0	74.0°	74.0°	9.0	66.5°	52.1	30.2	3.8	43.3	4.0	10.4	106.0	65.0	36.5	54.4
	XS	14.5"	27.5"	34.0	73.8°	74.0°	9.0	66.5°	55.1	31.3	4.5	43.3	4.2	11.0	109.2	65.8	39.0	56.3
	S	15.5"	27.5"	37.0	73.8°	74.0°	10.0	66.5°	57.9	31.3	4.5	43.3	4.2	11.0	112.1	69.2	41.5	57.2
	M	17.5"	29"	42.0	73.4°	74.0°	10.5	66.5°	61.5	30.8	6.0	43.8	4.6	11.0	116.3	74.7	44.0	60.9
	ML	18.5"	29"	43.5	73.4°	74.0°	11.0	66.5°	63.1	30.8	6.0	43.8	4.6	11.0	118.0	75.9	45.5	61.4
	L	19.5"	29"	45.0	73.4°	74.0°	11.5	66.5°	64.7	30.8	6.0	43.8	4.6	11.0	119.7	77.1	47.0	61.8
	XL	21.5"	29"	50.0	73.4°	74.0°	13.5	66.5°	67.8	30.8	6.0	43.8	4.6	11.0	123.0	79.1	49.5	63.7
	XXL	23"	29"	54.0	73.4°	74.0°	15.0	66.5°	70.7	30.8	6.0	43.8	4.6	11.0	126.1	81.6	52.0	65.1
Marlin+	XS		27.5"	34.0	73.8°	74.0°	9.0	66.5°	55.1	31.3	4.5	47.0	4.6	11.0	112.9	67.8	39.0	56.3
	S		27.5"	37.0	73.8°	74.0°	10.0	66.5°	58.4	31.3	4.5	47.0	4.6	11.0	116.6	71.0	41.5	59.0
	M		29"	42.0	73.8°	74.0°	10.5	66.5°	62.0	31.8	6.0	48.5	4.2	11.4	121.8	76.0	44.0	62.6
	L		29"	45.0	73.8°	74.0°	11.5	66.5°	65.2	31.8	6.0	48.5	4.2	11.4	125.1	77.1	47.0	63.5
	XL		29"	50.0	73.8°	74.0°	13.5	66.5°	68.2	31.8	6.0	48.5	4.2	11.4	128.4	77.5	49.5	65.3

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model			Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
Procaliber Alloy	S		29"	39.0	71.0°	74.3°	9.0	67.0°	57.7	30.9	6.4	43.0	4.3		111.0	74.7	40.5	61.4		
	M		29"	42.0	71.5°	74.3°	9.0	67.0°	59.8	30.9	6.4	43.0	4.3		113.5	74.9	43.0	61.4		
	ML		29"	44.0	72.0°	74.3°	9.0	67.0°	61.3	30.9	6.4	43.5	4.3		115.5	75.8	44.5	61.4		
	L		29"	46.0	72.5°	74.3°	9.0	67.0°	62.8	30.9	6.4	43.5	4.3		117.1	76.3	46.0	61.4		
	XL		29"	51.0	73.0°	74.3°	12.0	67.0°	67.7	30.9	6.4	44.0	4.3		122.7	79.1	50.0	64.2		
Procaliber Carbon	S	15.5"	29"	39.3	72.8°	73.8°	9.0	68.8°	57.0	31.3	6.0	43.2	4.2	10.0	107.8	71.5	39.5	60.0		
	M	17.5"	29"	41.9	72.8°	73.8°	9.0	68.8°	59.5	31.3	6.0	43.2	4.2	10.0	110.3	75.5	42.0	60.0		
	ML	18.5"	29"	44.4	72.8°	73.8°	9.0	68.8°	61.0	31.3	6.0	43.2	4.2	10.0	111.8	76.5	43.5	60.0		
	L	19.5"	29"	47.0	72.8°	73.8°	9.0	68.8°	62.5	31.3	6.0	43.2	4.2	10.0	113.3	78.4	45.0	60.0		
	XL	21.5"	29"	51.0	72.8°	73.8°	10.5	68.8°	65.9	31.3	6.0	43.2	4.2	10.0	116.8	81.4	48.0	61.4		
	XXL	23"	29"	54.5	72.8°	73.8°	12.0	68.8°	68.3	31.3	6.0	43.2	4.2	10.0	119.4	84.1	50.0	62.3		
Roscoe	XS		27.5"	34.0	73.1°	74.7°	9.0	65.0°	55.2	31.9	4.5	43.0	4.2	12.2	112.0	72.9	39.0	59.1		
	S		29"	36.0	73.1°	74.7°	9.0	65.0°	58.6	32.1	6.1	43.0	4.2	13.1	115.1	74.1	41.5	62.6		
	M		29"	42.0	73.1°	74.7°	10.0	65.0°	61.4	32.1	6.1	43.0	4.2	13.1	118.1	74.8	44.0	63.5		
	ML		29"	43.5	73.1°	74.7°	10.5	65.0°	63.0	32.2	6.1	43.0	4.2	13.1	119.8	74.2	45.5	63.9		
	L		29"	45.0	73.1°	74.7°	11.0	65.0°	64.6	32.1	6.1	43.0	4.2	13.1	121.5	75.5	47.0	64.4		
	XL		29"	50.0	73.1°	74.7°	13.5	65.0°	67.7	32.2	6.1	43.0	4.2	13.1	125.0	76.5	49.5	66.6		

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
Service	S	15.5"	29"	36.8	72.5°	73.5°	9.0	69.5°	56.7	31.1	5.8	43.8	4.2	9.3	107.1	74.1	38.9	60.2
	M	17.5"	29"	41.9	71.9°	73.0°	9.0	69.5°	60.2	31.1	5.8	43.8	4.2	9.3	110.0	74.8	41.8	60.2
	L	19.5"	29"	47.0	71.9°	73.0°	10.0	69.5°	63.8	31.0	5.8	43.8	4.2	9.3	113.7	75.7	45.1	61.1
	XL	21.5"	29"	52.1	71.9°	73.0°	12.0	69.5°	65.9	31.0	5.8	43.8	4.2	9.3	115.9	76.9	46.6	63.0
	XXL	23"	29"	55.9	71.9°	73.0°	12.0	69.5°	67.3	31.1	5.8	43.8	4.2	9.3	117.3	80.4	48.0	63.0
Service Electric	S	15.5"	27.5"	39.4		71.6°	13.0	67.6°	59.8	30.7	4.9	45.5	4.2	10.4	112.5	72.2	39.0	62.3
	M	17.5"	29"	41.9		71.7°	13.0	67.7°	61.7	32.4	4.9	45.5	5.1	9.8	115.5	79.5	40.6	63.9
	L	19.5"	29"	47.0		71.7°	14.0	67.7°	64.1	32.4	5.0	45.5	5.1	9.8	118.0	75.8	42.7	64.9
	XL	21.5"	29"	52.1		71.7°	16.0	67.7°	67.2	32.4	5.0	45.5	5.1	9.8	120.6	76.8	45.2	66.7
Stache Alloy	S	15.5"	29+	39.4	67.9°	72.4°	9.0	67.9°	59.0	31.7	6.8	42.0	5.1	10.1	108.9	77.5	38.9	63.7
	M	17.5"	29+	41.9	67.8°	72.3°	9.0	67.8°	61.8	31.8	6.7	42.0	5.1	10.2	111.7	77.5	41.5	63.5
	L	19.5"	29+	47.0	67.8°	72.3°	10.0	67.8°	65.0	31.7	6.8	42.0	5.1	10.2	114.9	78.9	44.4	64.5
	XL	21.5"	29+	52.1	67.8°	72.3°	11.0	67.8°	67.2	31.7	6.8	42.0	5.1	10.2	117.2	79.5	46.3	65.4
Stache Carbon	S	15.5"	29+	39.4	67.9°	72.4°	9.0	67.9°	59.0	31.7	6.8	42.0	5.1	10.1	108.9	76.2	38.9	63.7
	M	17.5"	29+	41.9	67.8°	72.3°	9.0	67.8°	61.8	31.8	6.7	42.0	5.1	10.2	111.7	76.0	41.5	63.5
	ML	18.5"	29+	44.5	67.8°	72.3°	10.0	67.8°	63.6	31.7	6.8	42.0	5.1	10.2	113.5	79.3	43.0	64.5
	L	19.5"	29+	47.0	67.8°	72.3°	10.0	67.8°	65.0	31.7	6.8	42.0	5.1	10.2	114.9	79.3	44.4	64.5
	XL	21.5"	29+	52.1	67.8°	72.3°	11.0	67.8°	67.2	31.7	6.8	42.0	5.1	10.2	117.2	79.5	46.3	65.4
Ticket DJ	L		26"	33.0	71.0°		12.0	70.0°	60.1	32.0	1.0	40.0	4.0	7.8	105.0	69.1	41.4	54.3
Ticket S Mino High	L		26"	33.1	75.8°		12.3	69.3°	56.3	33.9	0.6	39.8	4.0	8.8	108.3	38.3	43.3	54.7
Ticket S Mino Low	L		26"	33.1	75.0°		12.3	68.5°	56.5	33.0	0.3	40.0	4.0	8.8	108.5	37.5	42.6	54.7
Fuel EX Alloy Mino High	XS		27.5"	36.0	71.2°	78.9°	9.5	64.9°	51.6	33.7	2.1	43.4	4.4	11.9	114.4	72.0	40.4	57.2

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
	S		27.5"	38.0	71.1°	78.5°	9.5	64.8°	55.0	33.7	2.1	43.4	4.4	11.9	117.4	72.7	43.3	57.2
	S		29"	38.0	71.4°	79.2°	9.5	65.1°	55.3	34.3	3.1	43.3	4.4	12.5	118.5	74.3	43.1	60.8
	M		29"	41.0	71.4°	78.8°	10.0	65.1°	58.3	34.3	3.1	43.3	4.4	12.5	121.2	74.3	45.6	61.2
	ML		29"	42.0	71.4°	78.0°	10.0	65.1°	60.6	34.3	3.1	43.8	4.4	12.5	123.2	74.8	47.6	61.2
	L		29"	43.5	71.4°	77.7°	10.5	65.1°	62.6	34.3	3.1	43.8	4.4	12.5	124.9	75.4	49.1	61.7
	XL		29"	47.0	71.3°	77.1°	12.0	65.0°	66.0	34.3	3.0	44.3	4.4	12.5	128.6	77.4	52.1	63.0
	XXL		29"	50.0	71.3°	76.5°	13.5	65.0°	69.5	34.3	3.0	44.8	4.4	12.5	132.2	78.1	55.1	64.4
Fuel EX Alloy Mino Low	XS		27.5"	36.0	70.8°	78.6°	9.5	64.5°	51.6	33.2	2.5	43.5	4.4	12.2	114.5	71.7	40.0	57.4
	S		27.5"	38.0	70.8°	78.2°	9.5	64.5°	55.1	33.2	2.5	43.5	4.4	12.2	117.5	72.4	43.0	57.4
	S		29"	38.0	70.8°	78.6°	9.5	64.5°	55.4	33.5	3.8	43.5	4.4	12.9	118.6	73.7	42.5	61.2
	M		29"	41.0	70.8°	78.2°	10.0	64.5°	58.4	33.5	3.8	43.5	4.4	12.9	121.3	73.7	45.0	61.7
	ML		29"	42.0	70.8°	77.5°	10.0	64.5°	60.7	33.5	3.8	44.0	4.4	12.9	123.3	74.2	47.0	61.7
	L		29"	43.5	70.8°	77.2°	10.5	64.5°	62.7	33.5	3.8	44.0	4.4	12.9	125.0	74.8	48.5	62.1
	XL		29"	47.0	70.8°	76.6°	12.0	64.5°	66.2	33.5	3.8	44.5	4.4	12.9	128.7	76.7	51.5	63.5
	XXL		29"	50.0	70.8°	76.0°	13.5	64.5°	69.7	33.5	3.8	45.0	4.4	12.9	132.3	77.4	54.5	64.8

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
Fuel EX Carbon Mino High	XS		27.5"	36.0	71.2°	78.9°	9.5	64.9°	51.6	33.7	2.1	43.4	4.4	11.9	114.4	71.9	40.4	57.2
	S		27.5"	38.0	71.1°	78.5°	9.5	64.8°	55.0	33.7	2.1	43.4	4.4	11.9	117.4	72.8	43.3	57.2
	S		29"	38.0	71.4°	79.2°	9.5	65.1°	55.3	34.3	3.1	43.3	4.4	12.5	118.5	73.8	43.1	60.8
	M		29"	41.0	71.4°	78.8°	10.0	65.1°	58.3	34.3	3.1	43.3	4.4	12.5	121.2	74.4	45.6	61.2
	ML		29"	42.0	71.4°	78.0°	10.0	65.1°	60.6	34.3	3.1	43.8	4.4	12.5	123.2	75.1	47.6	61.2
	L		29"	43.5	71.4°	77.7°	10.5	65.1°	62.6	34.3	3.1	43.8	4.4	12.5	124.9	75.4	49.1	61.7
	XL		29"	47.0	71.3°	77.1°	12.0	65.0°	66.0	34.3	3.0	44.3	4.4	12.5	128.6	76.7	52.1	63.0
Fuel EX Carbon Mino Low	XS		27.5"	36.0	70.8°	78.6°	9.5	64.5°	51.6	33.2	2.5	43.5	4.4	12.2	114.5	71.6	40.0	57.4
	S		27.5"	38.0	70.8°	78.2°	9.5	64.5°	55.1	33.2	2.5	43.5	4.4	12.2	117.5	72.4	43.0	57.4
	S		29"	38.0	70.8°	78.6°	9.5	64.5°	55.4	33.5	3.8	43.5	4.4	12.9	118.6	73.2	42.5	61.2
	M		29"	41.0	70.8°	78.2°	10.0	64.5°	58.4	33.5	3.8	43.5	4.4	12.9	121.3	73.7	45.0	61.7
	ML		29"	42.0	70.8°	77.5°	10.0	64.5°	60.7	33.5	3.8	44.0	4.4	12.9	123.3	74.5	47.0	61.7
	L		29"	43.5	70.8°	77.2°	10.5	64.5°	62.7	33.5	3.8	44.0	4.4	12.9	125.0	74.8	48.5	62.1
	XL		29"	47.0	70.8°	76.6°	12.0	64.5°	66.2	33.5	3.8	44.5	4.4	12.9	128.7	76.0	51.5	63.5

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
Fuel EXe Mino High	S	15.5"	29"	38.0	69.3°	77.3°	10.0	65.3°	57.2	34.1	3.2	43.8	4.4	12.4	118.7	73.2	43.4	61.6
	M	17.5"	29"	41.0	69.8°	77.3°	11.0	65.3°	59.9	34.1	3.2	43.8	4.4	12.4	121.6	73.3	45.9	62.5
	L	19.5"	29"	43.5	70.8°	77.3°	11.0	65.3°	62.9	34.1	3.2	43.8	4.4	12.4	124.6	73.9	48.9	62.5
	XL	21.5"	29"	47.0	71.3°	77.3°	12.0	65.3°	65.6	34.1	3.2	43.8	4.4	12.4	127.6	75.9	51.4	63.4
Fuel EXe Mino Low	S	15.5"	29"	38.0	68.8°	76.8°	10.0	64.8°	57.3	33.4	3.9	44.0	4.4	12.7	118.8	72.6	42.8	62.0
	M	17.5"	29"	41.0	69.3°	76.8°	11.0	64.8°	60.0	33.4	3.9	44.0	4.4	12.7	121.7	72.7	45.3	62.9
	L	19.5"	29"	43.5	70.3°	76.8°	11.0	64.8°	63.0	33.4	3.9	44.0	4.4	12.7	124.7	73.3	48.3	62.9
	XL	21.5"	29"	47.0	70.8°	76.8°	12.0	64.8°	65.8	33.4	3.9	44.0	4.4	12.7	127.6	75.3	50.8	63.8
Powerfly HT Gen 4 / Powerfly Sport EQ Gen 3	XS	13.5"	27.5"	36.3		70.0°	12.0	65.0°	57.9	32.8	3.7	45.5	5.1	11.4	113.5	70.6	35.2	62.1
	S	15.5"	27.5"	39.4		71.5°	13.0	67.6°	59.8	30.7	4.9	45.5	4.2	10.1	112.5	72.1	39.0	62.3
	M	17.5"	29"	41.9		71.7°	13.0	67.7°	61.7	32.4	4.9	45.5	5.1	9.8	115.5	79.4	40.6	63.9
	L	19.5"	29"	47.0		71.7°	14.0	67.7°	64.1	32.4	5.0	45.5	5.1	9.8	118.0	81.6	42.7	64.8
	XL	21.5"	29"	52.1		71.7°	16.0	67.7°	67.2	32.4	5.0	45.5	5.1	9.8	121.2	81.8	45.2	66.7
Powerfly FS Gen 3 / Powerfly FS EQ Gen 3	XS	14.5"	27.5"	36.8	68.3°	76.0°	14.0	66.5°	55.4	33.2	2.4	46.8	4.4	10.7	117.0	69.1	40.5	59.9
	S	15.5"	27.5"	39.5	68.3°	76.0°	14.0	66.5°	56.4	33.2	2.4	46.8	4.4	10.7	118.0	69.1	41.5	59.9
	M	17.5"	29"	42.0	67.5°	76.0°	13.0	66.5°	58.9	33.5	3.9	47.0	4.4	11.4	120.6	71.2	43.0	63.7
	L	19.5"	29"	45.0	67.5°	76.0°	14.0	66.5°	62.1	33.5	3.9	47.0	4.4	11.4	124.0	71.6	46.0	64.6
	XL	21.5"	29"	50.0	67.5°	76.0°	14.0	66.5°	64.6	33.5	3.9	47.0	4.4	11.4	126.5	71.3	48.5	64.6

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
Rail Alloy Gen 3 Mino High	S	15.5"	29"	41.0	68.0°	75.4°	10.5	64.9°	58.7	34.4	2.9	44.7	4.3	12.7	119.5	74.8	42.5	62.3
	M	17.5"	29"	42.0	68.0°	75.4°	10.5	64.9°	61.1	34.4	2.9	44.7	4.3	12.7	122.0	77.8	45.0	62.2
	L	19.5"	29"	45.0	68.0°	75.4°	11.0	64.9°	63.3	34.4	2.9	44.7	4.3	12.7	124.3	76.7	47.0	62.7
	XL	21.5"	29"	50.0	68.0°	75.4°	12.0	64.9°	66.5	34.4	2.9	44.7	4.3	12.7	127.7	78.0	49.9	63.6
Rail Alloy Gen 3 Mino Low	S	15.5"	29"	41.0	67.6°	75.0°	10.5	64.5°	58.8	33.9	3.5	44.8	4.3	13.1	119.6	74.3	42.0	62.6
	M	17.5"	29"	42.0	67.6°	75.0°	10.5	64.5°	61.3	33.9	3.5	44.8	4.3	13.1	122.1	77.3	44.5	62.6
	L	19.5"	29"	45.0	67.6°	75.0°	11.0	64.5°	63.4	33.9	3.5	44.8	4.3	13.1	124.3	76.2	46.5	63.0
	XL	21.5"	29"	50.0	67.6°	75.0°	12.0	64.5°	66.6	33.9	3.5	44.8	4.3	13.1	127.8	77.5	49.5	63.9
Rail Carbon Gen 4 Mino High	S	15.5"	29"	41.0	71.2°	77.1°	10.5	64.6°	57.9	34.6	2.7	44.7	4.3	13.0	121.3	76.1	43.6	62.5
	M	17.5"	29"	42.0	71.2°	77.1°	11.0	64.6°	60.0	34.6	2.7	44.7	4.3	13.0	123.6	77.3	45.6	62.9
	L	19.5"	29"	45.0	71.2°	77.1°	12.5	64.6°	63.8	34.6	2.7	44.7	4.3	13.0	127.7	77.0	49.1	64.3
	XL	21.5"	29"	50.0	71.2°	77.1°	14.0	64.6°	67.1	34.6	2.7	44.7	4.3	13.0	131.3	76.8	52.1	65.6
Rail Carbon Gen 4 Mino Low	S	15.5"	29"	41.0	70.8°	76.7°	10.5	64.2°	58.0	34.1	3.3	44.8	4.3	13.3	121.4	75.6	43.2	62.8
	M	17.5"	29"	42.0	70.8°	76.7°	11.0	64.2°	60.1	34.1	3.3	44.8	4.3	13.3	123.6	76.8	45.2	63.3
	L	19.5"	29"	45.0	70.8°	76.7°	12.5	64.2°	63.9	34.1	3.3	44.8	4.3	13.3	127.8	76.5	48.7	64.6
	XL	21.5"	29"	50.0	70.8°	76.7°	14.0	64.2°	67.3	34.1	3.3	44.8	4.3	13.3	131.4	76.3	51.7	66.0

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
Remedy Alloy Mino High	S	15.5"	27.5"	39.4	68.5°	74.7°	9.5	66.1°	56.0	35.6	9.4	43.3	4.6	11.2	113.9	73.9	40.1	58.3
	M	17.5"	27.5"	41.9	68.5°	74.7°	10.0	66.1°	58.6	35.6	9.4	43.3	4.6	11.2	116.6	77.1	42.6	58.8
	ML	18.5"	27.5"	44.5	68.5°	74.7°	10.5	66.1°	60.3	35.6	9.4	43.3	4.6	11.2	118.3	77.3	44.1	59.2
	L	19.5"	27.5"	47.0	68.5°	74.7°	11.0	66.1°	62.4	35.6	9.4	43.3	4.6	11.2	120.5	77.0	46.1	59.7
	XL	21.5"	27.5"	52.1	68.5°	74.7°	12.5	66.1°	64.8	35.6	9.4	43.3	4.6	11.2	123.1	77.5	48.1	61.0
Remedy Alloy Mino Low	S	15.5"	27.5"	39.4	67.9°	74.2°	9.5	65.5°	56.2	34.9	1.6	43.5	4.6	11.5	114.0	73.4	39.5	58.7
	M	17.5"	27.5"	41.9	68.0°	74.2°	10.0	65.6°	58.8	34.9	1.6	43.5	4.6	11.5	116.7	76.6	42.0	59.2
	ML	18.5"	27.5"	44.5	68.0°	74.2°	10.5	65.6°	60.4	34.9	1.6	43.5	4.6	11.5	118.4	76.8	43.5	59.6
	L	19.5"	27.5"	47.0	68.0°	74.2°	11.0	65.6°	62.5	34.9	1.6	43.5	4.6	11.5	120.6	76.5	45.5	60.1
	XL	21.5"	27.5"	52.1	68.0°	74.2°	12.5	65.6°	64.9	34.9	1.6	43.5	4.6	11.5	123.2	76.9	47.5	61.5
Remedy Carbon Mino High	S	15.5"	27.5"	39.4	68.5°	74.7°	9.5	66.1°	56.0	35.6	9.4	43.3	4.6	11.2	113.9	74.3	40.1	58.3
	M	17.5"	27.5"	41.9	68.5°	74.7°	10.0	66.1°	58.6	35.6	9.4	43.3	4.6	11.2	116.6	77.1	42.6	58.8
	ML	18.5"	27.5"	44.5	68.5°	74.7°	10.5	66.1°	60.3	35.6	9.4	43.3	4.6	11.2	118.3	77.3	44.1	59.2
	L	19.5"	27.5"	47.0	68.5°	74.7°	11.0	66.1°	62.4	35.6	9.4	43.3	4.6	11.2	120.5	77.0	46.1	59.7
	XL	21.5"	27.5"	52.1	68.5°	74.7°	12.5	66.1°	64.8	35.6	9.4	43.3	4.6	11.2	123.1	78.2	48.1	61.0
Remedy Carbon Mino Low	S	15.5"	27.5"	39.4	67.9°	74.2°	9.5	65.5°	56.2	34.9	1.6	43.5	4.6	11.5	114.0	73.8	39.5	58.7
	M	17.5"	27.5"	41.9	68.0°	74.2°	10.0	65.6°	58.8	34.9	1.6	43.5	4.6	11.5	116.7	76.6	42.0	59.2
	ML	18.5"	27.5"	44.5	68.0°	74.2°	10.5	65.6°	60.4	34.9	1.6	43.5	4.6	11.5	118.4	76.8	43.5	59.6
	L	19.5"	27.5"	47.0	68.0°	74.2°	11.0	65.6°	62.5	34.9	1.6	43.5	4.6	11.5	120.6	76.5	45.5	60.1
	XL	21.5"	27.5"	52.1	68.0°	74.2°	12.5	65.6°	64.9	34.9	1.6	43.5	4.6	11.5	123.2	77.6	47.5	61.5

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
Session Alloy Mino High	R1		29"	42.5	61.6°	77.1°	11.7	63.6°	58.6	35.9	1.2	43.5	4.6	13.1	124.3	75.5	44.7	63.4
	R2		29"	42.5	61.6°	77.1°	11.7	63.6°	61.7	35.9	1.2	44.1	4.6	13.1	127.4	75.9	47.2	63.4
	R3		29"	42.5	61.6°	77.1°	11.7	63.6°	65.2	35.9	1.2	44.8	4.6	13.2	130.9	75.7	49.9	63.4
Session Alloy Mino Low	R1		29"	42.5	61.0°	76.5°	11.7	63.0°	58.7	35.0	2.1	43.9	4.6	13.6	124.6	74.7	44.0	63.9
	R2		29"	42.5	61.0°	76.5°	11.7	63.0°	61.8	35.0	2.1	44.5	4.6	13.6	127.7	75.1	46.5	63.9
	R3		29"	42.5	61.0°	76.5°	11.7	63.0°	65.3	35.0	2.1	45.2	4.6	13.6	131.2	74.9	49.3	63.9
Slash Gen 6	S	15.5	27.5"	39.0	74.0°	78.1°	10.0	63.5°	54.8	35.2	1.0	42.9	4.3	13.2	119.5	72.7	43.0	58.8
	M	17.5	29"/27.5"	40.0	73.8°	77.8°	10.0	63.3°	57.8	35.1	2.7	42.9	4.3	14.3	122.4	76.6	44.8	62.3
	ML	18.5	29"/27.5"	42.0	73.8°	77.3°	11.0	63.3°	60.5	35.1	2.7	43.4	4.3	14.3	125.3	76.6	46.8	63.2
	L	19.5	29"/27.5"	43.5	73.8°	77.1°	12.0	63.3°	62.8	35.1	2.7	43.4	4.3	14.3	127.8	76.7	48.8	64.1
	XL	21.5	29"/27.5"	47.0	73.8°	76.7°	14.0	63.3°	65.8	35.1	2.7	43.9	4.3	14.3	131.2	76.8	51.3	65.9
Supercaliber SLR Gen 2 100mm Fork	S		29"	39.5	71.0°	75.0°	9.0	68.0°	56.9	32.3	4.6	43.5	4.3	10.9	110.9		41.5	58.6
	M		29"	42.0	71.5°	75.0°	9.0	68.0°	59.0	32.3	4.6	43.5	4.3	10.9	113.4		44.0	58.6
	ML		29"	44.0	71.5°	75.0°	9.0	68.0°	60.3	32.3	4.6	43.5	4.3	10.9	114.9		45.5	58.6
	L		29"	46.0	72.0°	75.0°	10.0	68.0°	62.1	32.3	4.6	43.5	4.3	10.9	116.8		47.0	59.5
	XL		29"	52.5	71.9°	74.9°	12.5	67.9°	66.2	32.3	4.6	43.5	4.3	10.9	121.3		50.5	61.8
Supercaliber SLR Gen 2 110mm Fork	S		29"	39.5	70.5°	74.5°	9.0	67.5°	57.1	32.7	4.6	43.5	4.3	10.9	111.3	76.0	41.0	59.0
	M		29"	42.0	71.0°	74.5°	9.0	67.5°	59.2	32.7	4.6	43.5	4.3	10.9	113.8	77.2	43.5	59.0
	ML		29"	44.0	71.0°	74.5°	9.0	67.5°	60.5	32.7	4.6	43.5	4.3	10.9	115.3	77.2	45.0	59.0
	L		29"	46.0	71.5°	74.5°	10.0	67.5°	62.2	32.7	4.6	43.5	4.3	10.9	117.2	77.2	46.5	59.9
	XL		29"	52.5	71.5°	74.5°	12.5	67.5°	66.3	32.7	4.6	43.5	4.3	10.9	121.7	77.2	50.0	62.2
Supercaliber SLR Gen 2	S		29"	39.5	70.0°	74.0°	9.0	67.0°	57.2	33.0	4.6	43.5	4.3	10.9	111.7		40.5	59.3

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
120mm Fork	M		29"	42.0	70.5°	74.0°	9.0	67.0°	59.3	33.0	4.6	43.5	4.3	10.9	114.2		43.0	59.3
	ML		29"	44.0	70.5°	74.0°	9.0	67.0°	60.6	33.0	4.6	43.5	4.3	10.9	115.7		44.5	59.3
	L		29"	46.0	71.0°	74.0°	10.0	67.0°	62.4	33.0	4.6	43.5	4.3	10.9	117.6		46.0	60.3
	XL		29"	52.5	71.1°	74.1°	12.5	67.1°	66.5	33.0	4.6	43.5	4.3	10.9	122.0		49.5	62.6
Top Fuel Gen 3 Mino High	XS	13.5"	27.5"	35.6	70.9°	76.4°	9.5	66.4°	53.8	34.0	1.5	43.4	4.4	10.7	112.1	69.9	40.4	55.5
120mm Fork	S	15.5"	29"	39.5	70.4°	76.4°	10.0	66.4°	56.7	34.3	3.1	43.4	4.4	11.5	115.0	71.9	42.4	59.2
	M	17.5"	29"	42.0	70.4°	76.4°	10.0	66.4°	59.7	34.3	3.1	43.4	4.4	11.5	118.0	74.0	45.4	59.2
	ML	18.5"	29"	43.5	70.4°	76.4°	10.5	66.4°	61.4	34.3	3.1	43.4	4.4	11.5	119.7	74.5	46.9	59.7
	L	19.5"	29"	45.0	70.4°	76.4°	11.0	66.4°	63.0	34.3	3.1	43.4	4.4	11.5	121.4	75.0	48.4	60.1
	XL	21.5"	29"	50.0	70.4°	76.4°	12.5	66.4°	65.3	34.3	3.1	43.4	4.4	11.5	124.0	76.0	50.4	61.5
	XXL	23"	29"	54.0	70.4°	76.4°	13.5	66.4°	67.5	34.3	3.0	43.4	4.4	11.5	126.5	77.0	52.4	62.4
Top Fuel Gen 3 Mino Low	XS	13.5"	27.5"	35.6	70.5°	76.0°	9.5	66.0°	53.9	33.6	2.0	43.5	4.4	11.0	112.2	69.5	40.0	55.8
120mm Fork	S	15.5"	29"	39.5	70.0°	76.0°	10.0	66.0°	56.8	33.8	3.6	43.5	4.4	11.8	115.1	71.5	42.0	59.5
	M	17.5"	29"	42.0	70.0°	76.0°	10.0	66.0°	59.8	33.8	3.6	43.5	4.4	11.8	118.1	73.5	45.0	59.5
	ML	18.5"	29"	43.5	70.0°	76.0°	10.5	66.0°	61.5	33.8	3.6	43.5	4.4	11.8	119.8	74.0	46.5	60.0
	L	19.5"	29"	45.0	70.0°	76.0°	11.0	66.0°	63.1	33.8	3.6	43.5	4.4	11.8	121.5	74.5	48.0	60.5
	XL	21.5"	29"	50.0	70.0°	76.0°	12.5	66.0°	65.4	33.8	3.6	43.5	4.4	11.8	124.1	75.5	50.0	61.8
	XXL	23"	29"	54.0	70.0°	76.0°	13.5	66.0°	67.6	33.8	3.6	43.5	4.4	11.8	126.5	76.5	52.0	62.7

2024 Mountain Bike Geometry



All measurements in cm unless otherwise noted

Model	Frame Size Letter	Frame Size Number	Wheel Size	A - Seat Tube Length	B - Seat Tube Angle	Effective Seat Tube Angle	C - Head Tube Length	D - Head Tube Angle	E - Effective Top Tube Length	F - Bottom Bracket Height	G - Bottom Bracket Drop	H - Chainstay Length	I - Fork Offset	J - Fork Trail	K - Wheelbase	L - Frame Standover	M - Frame Reach	N - Frame Stack
Top Fuel Gen 3 Mino High 130mm Fork	XS	13.5"	27.5"	35.6	70.4°	75.9°	9.5	65.9°	53.9	34.4	1.2	43.4	4.4	11.1	112.5	70.3	39.9	55.8
	S	15.5"	29"	39.5	69.9°	75.9°	10.0	65.9°	56.9	34.6	2.7	43.4	4.3	12.0	115.3	72.4	41.9	59.6
	M	17.5"	29"	42.0	69.9°	75.9°	10.0	65.9°	59.9	34.6	2.7	43.4	4.3	12.0	118.3	74.4	44.9	59.6
	ML	18.5"	29"	43.5	69.9°	75.9°	10.5	65.9°	61.5	34.6	2.7	43.4	4.3	12.0	120.0	74.9	46.4	60.0
	L	19.5"	29"	45.0	69.9°	75.9°	11.0	65.9°	63.1	34.6	2.7	43.4	4.3	12.0	121.7	75.4	47.9	60.5
	XL	21.5"	29"	50.0	69.9°	75.9°	12.5	65.9°	65.4	34.6	2.7	43.4	4.3	12.0	124.4	76.4	49.9	61.9
	XXL	23"	29"	54.0	75.9°	69.9°	13.5	65.9°	67.7	34.6	2.7	43.4	4.3	11.2	126.8	76.4	51.9	63.0
Top Fuel Gen 3 Mino Low 130mm Fork	XS	13.5"	27.5"	35.6	70.0°	75.5°	9.5	65.5°	54.0	33.9	1.6	43.5	4.4	11.3	112.6	69.9	39.5	56.1
	S	15.5"	29"	39.5	69.5°	75.5°	10.0	65.5°	57.0	34.1	3.2	43.5	4.3	12.3	115.4	71.9	41.5	59.9
	M	17.5"	29"	42.0	69.5°	75.5°	10.0	65.5°	60.0	34.1	3.3	43.5	4.3	12.3	118.4	73.9	44.5	59.9
	ML	18.5"	29"	43.5	69.5°	75.5°	10.5	65.5°	61.6	34.1	3.3	43.5	4.3	12.3	120.1	74.4	46.0	60.4
	L	19.5"	29"	45.0	69.6°	75.6°	11.0	65.6°	63.2	34.1	3.3	43.5	4.3	12.3	121.8	74.9	47.5	60.8
	XL	21.5"	29"	50.0	69.6°	75.6°	12.5	65.6°	65.5	34.1	3.3	43.5	4.3	12.3	124.4	75.9	49.5	62.2
	XXL	23"	29"	54.0	75.6°	69.6°	13.5	65.6°	67.8	34.1	3.3	43.5	4.3	12.2	126.8	75.9	51.5	63.1