



# ROAD GEOMETRY

Models	Frame Size*	Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	G - Bottom bracket drop	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover	M - Frame reach	N - Frame stack	Seat height maximum	Seat height minimum
Madone H1 Fit	50 cm	700c	45.3	74.6°	10.0	72.1°	52.2	7.2	41.0	4.5	6.1	97.4	69.6	38.3	51.1	58.5	67.5	
	52 cm	700c	48.2	74.2°	11.0	72.8°	53.5	7.2	41.0	4.5	5.7	97.7	72.0	38.8	52.3	61.5	70.5	
	54 cm	700c	49.6	73.7°	12.0	73.0°	54.4	7.0	41.0	4.5	5.6	98.1	73.3	39.0	53.1	64.0	73.0	
	56 cm	700c	52.5	73.3°	14.0	73.5°	56.0	7.0	41.0	4.0	5.8	98.3	75.8	39.5	55.4	67.0	76.0	
	58 cm	700c	55.3	73.0°	16.0	73.8°	57.3	6.8	41.1	4.0	5.6	99.2	78.3	40.0	57.2	69.0	78.0	
	60 cm	700c	57.3	72.8°	18.0	73.9°	58.6	6.8	41.1	4.0	5.6	100.1	80.1	40.4	59.1	71.0	80.0	
	62 cm	700c	59.3	72.5°	20.0	73.9°	59.8	6.8	41.2	4.0	5.5	101.0	82.0	40.7	61.1	73.0	82.0	
	50 cm	700c	47.6	74.6°	13.0	72.1°	52.1	7.2	41.0	4.5	6.1	97.4	70.7	37.4	54.0	58.5	67.5	
Madone H2 Fit	52 cm	700c	49.3	74.2°	14.0	72.8°	53.2	7.2	41.0	4.5	5.7	97.7	72.9	37.9	55.2	61.5	70.5	
	54 cm	700c	50.6	73.7°	15.5	73.0°	54.3	7.0	41.0	4.5	5.6	98.1	74.2	38.1	56.0	64.0	73.0	
	56 cm	700c	53.3	73.3°	17.0	73.5°	56.0	7.0	41.0	4.0	5.8	98.3	76.7	38.7	58.2	67.0	76.0	
	58 cm	700c	55.3	73.0°	19.0	73.8°	57.3	6.8	41.1	4.0	5.6	99.2	78.6	39.1	60.1	69.0	78.0	
	60 cm	700c	57.3	72.8°	21.0	73.9°	58.6	6.8	41.1	4.0	5.6	100.1	80.4	39.5	62.0	71.0	80.0	
	62 cm	700c	59.3	72.5°	23.0	73.9°	59.8	6.8	41.2	4.0	5.5	101.0	82.2	39.8	63.9	73.0	82.0	
	Domane	44 cm	700c	39.0	74.6°	9.5	70.3°	50.1	8.0	42.0	5.3	6.6	98.3	65.7	36.0	51.0	53.5	63.0
		47 cm	700c	42.0	74.6°	11.0	71.0°	50.9	8.0	42.0	5.3	6.1	98.6	68.6	36.4	52.7	55.5	65.0
50 cm		700c	45.0	74.6°	13.0	71.1°	51.9	8.0	42.0	5.3	6.0	99.6	71.6	36.8	54.6	58.5	68.0	
52 cm		700c	47.5	74.2°	14.5	71.3°	53.0	8.0	42.0	5.3	5.9	100.3	73.5	37.1	56.1	61.5	71.0	
54 cm		700c	50.0	73.7°	16.0	71.3°	54.2	8.0	42.0	5.3	5.9	101.0	75.4	37.4	57.5	64.0	73.5	
56 cm		700c	52.5	73.3°	17.5	71.9°	55.4	7.8	42.0	4.8	6.1	100.8	77.6	37.7	59.1	67.0	76.5	
58 cm		700c	54.8	73.0°	19.5	72.0°	56.7	7.8	42.5	4.8	6.0	102.2	79.6	38.0	61.1	69.0	78.5	
60 cm		700c	56.7	72.8°	22.0	72.1°	57.9	7.5	42.5	4.8	5.9	103.2	81.7	38.3	63.2	71.0	80.5	
62 cm		700c	58.6	72.5°	24.5	72.1°	59.3	7.5	42.5	4.8	5.9	104.2	83.5	38.6	65.6	73.0	82.5	
Speed Concept		XS	650c	47.8	78.0°	9.0	72.0°	46.9	5.5	37.4	4.0	6.0	91.0	72.6	37.0	46.8	57.4	72.3
	S	700c	50.3	78.0°	6.5	72.2°	49.5	8.0	40.0	4.5	6.1	96.1	75.0	39.0	49.2	59.9	74.7	
	M	700c	52.9	78.0°	9.0	72.5°	51.8	8.0	40.0	4.5	6.0	98.5	77.5	40.8	51.7	62.5	77.2	
	L	700c	55.3	78.0°	11.5	72.5°	54.1	8.0	40.0	4.5	6.0	101.0	79.9	42.6	54.1	64.9	79.6	
	XL	700c	57.8	78.0°	14.0	72.5°	56.5	8.0	40.0	4.5	6.0	103.7	82.3	44.5	56.5	67.3	82.0	
Boone	50 cm	700c	47.6	75.0°	11.0	71.0°	51.8	7.0	42.5	4.5	7.4	100.1	74.7	37.5	53.4	58.5	67.5	
	52 cm	700c	49.3	74.5°	12.3	71.5°	53.1	7.0	42.5	4.5	7.1	100.5	76.1	37.9	54.7	61.5	70.5	
	54 cm	700c	51.3	74.0°	13.8	72.0°	54.4	6.8	42.5	4.5	6.7	101.0	77.9	38.3	56.2	64.0	73.0	
	56 cm	700c	53.3	73.6°	15.7	72.0°	55.8	6.8	42.5	4.5	6.7	102.0	79.6	38.7	58.0	67.0	76.0	
	58 cm	700c	55.3	73.3°	17.6	72.3°	57.0	6.5	42.5	4.5	6.6	102.8	81.6	39.1	59.7	69.0	78.0	
	61 cm	700c	58.3	73.0°	20.5	72.3°	58.8	6.5	42.5	4.5	6.6	104.3	84.3	39.7	62.4	72.0	81.0	
	Crockett	47 cm	700c	44.4	75.3°	9.5	70.8°	50.7	7.0	42.5	4.5	7.5	99.5	72.4	37.1	51.9		
50 cm		700c	47.6	75.0°	11.0	71.0°	51.8	7.0	42.5	4.5	7.4	100.1	74.7	37.5	53.4			
52 cm		700c	49.3	74.5°	12.3	71.5°	53.1	7.0	42.5	4.5	7.1	100.5	76.1	37.9	54.7			
54 cm		700c	51.3	74.0°	13.8	72.0°	54.4	6.8	42.5	4.5	6.7	101.0	77.9	38.3	56.2			
56 cm		700c	53.3	73.6°	15.7	72.0°	55.8	6.8	42.5	4.5	6.7	102.0	79.6	38.7	58.0			
58 cm		700c	55.3	73.3°	17.6	72.3°	57.0	6.5	42.5	4.5	6.6	102.8	81.6	39.1	59.7			
61 cm		700c	58.3	73.0°	20.5	72.3°	58.8	6.5	42.5	4.5	6.6	104.3	84.3	39.7	62.4			
Madone H15		50 cm	700c	45.3	74.6°	11.1	72.1°	52.1	7.2	41.0	4.5	6.2	97.4	71.1	37.8	52.1		
	52 cm	700c	48.3	74.2°	12.1	72.8°	53.4	7.2	41.0	4.5	5.8	97.7	73.2	38.3	53.3			
	54 cm	700c	49.6	73.7°	13.1	73.0°	54.3	7.0	41.0	4.5	5.6	98.1	74.4	38.6	54.1			
	56 cm	700c	52.5	73.3°	15.1	73.5°	55.9	7.0	41.0	4.0	5.8	98.3	76.8	39.1	56.3			
	58 cm	700c	55.3	73.0°	17.1	73.8°	57.4	6.8	41.1	4.0	5.7	99.2	79.3	39.6	58.1			
	60 cm	700c	57.3	72.8°	19.1	73.9°	58.6	6.8	41.1	4.0	5.6	100.1	81.1	39.9	60.1			
	62 cm	700c	59.3	72.5°	21.1	73.9°	59.8	6.8	41.2	4.0	5.6	101	82.9	40.3	62.0			
	Checkpoint Carbon	49 cm	700c	49	75.0°	9.0	71.4°	51.5	7.8	42.5	4.9	6.6	99.5	72.3	37.3	53.2	66.5	57.5
52 cm		700c	52	74.0°	10.7	71.6°	53.6	7.8	42.5	4.9	6.5	100.5	74.9	37.9	54.9	70.0	61.0	
54 cm		700c	54	73.5°	12.6	71.8°	55.1	7.6	42.5	4.9	6.4	101.4	77.5	38.3	56.7	73.0	64.0	
56 cm		700c	56	73.0°	14.5	72.2°	56.6	7.6	42.5	4.9	6.1	102.0	79.5	38.7	58.6	76.0	67.0	
58 cm		700c	58	73.0°	17.1	72.3°	57.7	7.4	42.5	4.9	6.1	103.2	81.7	39.1	60.9	78.0	69.0	
61 cm		700c	61	73.0°	20.0	72.6°	59.2	7.4	42.5	4.9	5.9	104.4	84.6	39.7	63.8	81.0	72.0	
Checkpoint	49 cm	700c	49	75.0°	9.0	71.4°	51.5	7.8	42.5	4.9	6.6	99.5	74.9	37.3	53.2			
	52 cm	700c	52	74.0°	10.7	71.6°	53.6	7.8	42.5	4.9	6.5	100.5	77	37.9	54.9			
	54 cm	700c	54	73.5°	12.6	71.8°	55.1	7.6	42.5	4.9	6.4	101.4	78.9	38.3	56.7			
	56 cm	700c	56	73.0°	14.5	72.2°	56.6	7.6	42.5	4.9	6.1	102.0	80.8	38.7	58.6			
	58 cm	700c	58	73.0°	17.1	72.3°	57.7	7.4	42.5	4.9	6.1	103.2	82.9	39.1	60.9			
	61 cm	700c	61	73.0°	20.0	72.6°	59.2	7.4	42.5	4.9	5.9	104.4	85.8	39.7	63.8			
1120	15.5 in	29"	39.4	73.5°	10.0	70.4°	56.0	31.4	7.6	44.0	5.1	8.5	108.2	77.8	39.6	63.4		
	17.5 in	29"	41.9	73.5°	10.0	70.4°	58.6	31.5	7.5	44.0	5.1	8.5	110.8	79.1	42.2	63.4		
	19.5 in	29"	47.0	73.5°	11.0	70.3°	61.9	31.5	7.5	44.0	5.1	8.5	114.2	79.2	45.1	64.2		
	21.5 in	29"	52.1	73.5°	12.0	70.3°	64.3	31.5	7.5	44.0	5.1	8.6	116.6	79.2	47.1	65.1		
920	49 cm	29"	44.0	74.5°	9.5	70.0°	54.0	28.3	8.5	46.5	5.5	7.5	107.2	72.2	38.5	55.6		
	52 cm	29"	47.0	74.0°	10.5	70.5°	55.1	28.3	8.5	46.5	5.5	7.2	107.4	74.3	38.8	56.7		
	54 cm	29"	49.0	73.8°	12.0	71.0°	56.2	28.3	8.5	46.5	5.5	6.8	107.9	76.0	39.2	58.3		
	56 cm	29"	51.0	73.3°	14.5	71.3°	57.8	28.3	8.5	46.5	5.5	6.7	108.8	77.8	39.5	60.8		
	58 cm	29"	53.0	73.0°	16.5	71.3°	59.4	28.3	8.5	46.5	5.5	6.7	110.0	79.6	40.2	62.7		
	61 cm	29"	56.0	72.8°	18.0	71.5°	60.4	28.3	8.5	46.5	5.5	6.5	110					

# MOUNTAIN GEOMETRY

Models	Frame Size*	Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	G - Bottom bracket drop	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover	M - Frame reach	N - Frame stack	Seat height maximum	Seat height minimum
Top Fuel Low geometry**	15.5 in	27.5"	39.4	69.5°	10.0	69.9°	55.8	33.0	2.5	42.7	4.7	8.0	106.4	73.2	39.2	56.1		
	17.5 in	29"	41.9	68.5°	9.0	70.0°	59.3	33.0	3.9	43.5	5.1	8.0	111.1	72.4	42.7	57.7		
	18.5 in	29"	44.5	68.5°	9.0	70.0°	60.9	33.0	3.9	43.5	5.1	8.0	112.7	71.9	44.3	57.7		
	19.5 in	29"	47.0	68.5°	10.0	70.0°	62.5	33.0	3.9	43.5	5.1	8.0	114.4	71.9	45.7	58.7		
	21.5 in	29"	49.5	68.5°	12.0	70.0°	64.6	33.0	3.9	43.5	5.1	8.0	116.6	71.9	47.2	60.6		
Top Fuel High geometry**	15.5 in	27.5"	39.4	70.5°	10.0	70.9°	55.6	34.1	1.4	42.4	4.7	7.3	106.3	74.1	40.1	55.4		
	17.5 in	29"	41.9	69.4°	9.0	70.9°	59.3	34.1	2.8	43.2	5.1	7.4	110.9	73.4	43.6	57.0		
	18.5 in	29"	44.5	69.4°	9.0	70.9°	60.6	34.1	2.8	43.2	5.1	7.4	112.5	72.9	45.2	57.0		
	19.5 in	29"	47.0	69.4°	10.0	70.9°	62.3	34.1	2.7	43.2	5.1	7.4	114.3	72.9	46.6	58.0		
	21.5 in	29"	49.5	69.4°	12.0	70.9°	64.6	34.1	2.7	43.2	5.1	7.4	116.5	72.9	48.1	59.8		
Fuel EX Carbon 29 Low geometry**	15.5 in	29"	39.4	65.5°	10.0	67.0°	56.6	33.5	3.9	43.5	5.1	10.3	112.2	76.0	39.1	60.9		
	17.5 in	29"	41.9	65.5°	10.0	67.0°	60.1	33.5	3.9	43.5	5.1	10.3	115.7	74.0	42.6	60.9		
	18.5 in	29"	44.0	65.5°	10.0	67.0°	61.8	33.5	3.9	43.5	5.1	10.3	117.4	73.5	44.3	60.9		
	19.5 in	29"	47.0	65.5°	10.0	67.0°	63.3	33.5	3.9	43.5	5.1	10.3	118.9	73.0	45.8	60.9		
	21.5 in	29"	51.0	65.5°	11.0	67.0°	65.7	33.5	3.9	43.5	5.1	10.3	121.5	74.0	48.0	61.8		
Fuel EX Carbon 29 High geometry**	15.5 in	29"	39.4	66.2°	10.0	67.7°	56.5	34.4	3.0	43.2	5.1	9.9	112.1	76.7	39.9	60.4		
	17.5 in	29"	41.9	66.2°	10.0	67.7°	59.9	34.4	3.0	43.2	5.1	9.9	115.6	74.7	43.3	60.3		
	18.5 in	29"	44.0	66.2°	10.0	67.7°	61.6	34.4	3.0	43.2	5.1	9.9	117.3	74.2	45.0	60.3		
	19.5 in	29"	47.0	66.2°	10.0	67.7°	63.1	34.4	3.0	43.2	5.1	9.9	118.8	73.7	46.5	60.3		
	21.5 in	29"	51.0	66.2°	11.0	67.7°	65.7	34.4	3.0	43.2	5.1	9.9	121.4	74.7	48.7	61.2		
Fuel EX Aluminum 29 Low geometry**	15.5 in	29"	39.4	65.5°	10.0	67.0°	56.6	33.5	3.9	43.3	5.1	10.3	112.2	76.0	39.1	60.9		
	17.5 in	29"	41.9	65.5°	10.0	67.0°	60.1	33.5	3.9	43.3	5.1	10.3	115.7	74.0	42.6	60.9		
	18.5 in	29"	44.0	65.5°	10.0	67.0°	61.8	33.5	3.9	43.3	5.1	10.3	117.4	73.5	44.3	60.9		
	19.5 in	29"	47.0	65.5°	10.0	67.0°	63.3	33.5	3.9	43.3	5.1	10.3	118.9	73.0	45.8	60.9		
	21.5 in	29"	51.0	65.5°	11.0	67.0°	65.7	33.5	3.9	43.3	5.1	10.3	121.5	74.0	48.0	61.8		
Fuel EX Aluminum 29 High geometry**	15.5 in	29"	39.4	66.2°	10.0	67.7°	56.5	34.4	3.0	43.2	5.1	9.9	112.1	76.7	39.9	60.4		
	17.5 in	29"	41.9	66.2°	10.0	67.7°	60.0	34.4	3.0	43.2	5.1	9.9	115.6	74.7	43.3	60.3		
	18.5 in	29"	44.0	66.2°	10.0	67.7°	61.7	34.4	3.0	43.2	5.1	9.9	117.3	74.2	45.0	60.3		
	19.5 in	29"	47.0	66.2°	10.0	67.7°	63.2	34.4	3.0	43.2	5.1	9.9	118.8	73.7	46.5	60.3		
	21.5 in	29"	51.0	66.2°	11.0	67.7°	65.7	34.4	3.0	43.2	5.1	9.9	121.4	74.7	48.7	61.2		
Fuel EX Carbon 275Plus Low geometry**	15.5 in	27.5"	39.4	65.1°	10.0	66.6°	56.6	32.3	3.9	43.2	5.1	10.6	112.2	76.0	38.7	61.3		
	17.5 in	27.5"	41.9	65.1°	10.0	66.6°	60.1	32.3	3.9	43.2	5.1	10.6	115.7	74.0	42.2	61.2		
	18.5 in	27.5"	44.0	65.1°	10.0	66.6°	61.8	32.3	3.9	43.2	5.1	10.6	117.4	73.5	43.9	61.2		
	19.5 in	27.5"	47.0	65.1°	10.0	66.6°	63.3	32.3	3.9	43.2	5.1	10.6	118.9	73.0	45.4	61.2		
	21.5 in	27.5"	51.0	65.1°	11.0	66.6°	65.7	32.3	3.9	43.2	5.1	10.6	121.5	74.0	47.6	62.1		
Fuel EX Carbon 275Plus High geometry**	15.5 in	27.5"	39.4	65.7°	10.0	67.2°	56.5	32.9	3.0	43.3	5.1	10.2	112.1	76.7	39.5	60.7		
	17.5 in	27.5"	41.9	65.7°	10.0	67.2°	60.0	32.9	3.0	43.3	5.1	10.2	115.6	74.7	43	60.6		
	18.5 in	27.5"	44.0	65.7°	10.0	67.2°	61.7	32.9	3.0	43.3	5.1	10.2	117.3	74.2	44.6	60.6		
	19.5 in	27.5"	47.0	65.7°	10.0	67.2°	63.2	32.9	3.0	43.3	5.1	10.2	118.8	73.7	46.1	60.6		
	21.5 in	27.5"	51.0	65.7°	11.0	67.2°	65.7	32.9	3.0	43.3	5.1	10.2	121.4	74.7	48.3	61.5		
Fuel EX Aluminum 275Plus Low geometry**	15.5 in	27.5"	39.4	65.1°	10.0	66.6°	56.6	32.3	3.9	43.2	5.1	10.6	112.2	76.0	38.7	61.3		
	17.5 in	27.5"	41.9	65.1°	10.0	66.6°	60.1	32.3	3.9	43.2	5.1	10.6	115.7	74.0	42.2	61.2		
	18.5 in	27.5"	44.0	65.1°	10.0	66.6°	61.8	32.3	3.9	43.2	5.1	10.6	117.4	73.5	43.9	61.2		
	19.5 in	27.5"	47.0	65.1°	10.0	66.6°	63.3	32.3	3.9	43.2	5.1	10.6	118.9	73.0	45.4	61.2		
	21.5 in	27.5"	51.0	65.1°	11.0	66.6°	65.7	32.3	3.9	43.2	5.1	10.6	121.5	74.0	47.6	62.1		
Fuel EX Aluminum 275Plus High geometry**	15.5 in	27.5"	39.4	65.7°	10.0	67.2°	56.5	32.9	3.0	43.3	5.1	10.2	112.1	76.7	39.5	60.7		
	17.5 in	27.5"	41.9	65.7°	10.0	67.2°	60.0	32.9	3.0	43.3	5.1	10.2	115.6	74.7	43	60.6		
	18.5 in	27.5"	44.0	65.7°	10.0	67.2°	61.7	32.9	3.0	43.3	5.1	10.2	117.3	74.2	44.6	60.6		
	19.5 in	27.5"	47.0	65.7°	10.0	67.2°	63.2	32.9	3.0	43.3	5.1	10.2	118.8	73.7	46.1	60.6		
	21.5 in	27.5"	51.0	65.7°	11.0	67.2°	65.7	32.9	3.0	43.3	5.1	10.2	121.4	74.7	48.3	61.5		
Fuel EX Carbon Womens Low geometry**	14 in	27.5"	35.6	65.8°	9.0	67.0°	54.4	33.0	2.6	43.4	4.3	10.4	108.8	69.7	37.1	57.1		
	15.5 in	27.5"	39.4	65.8°	10.0	67.0°	56.3	33.0	2.6	43.4	4.3	10.4	110.7	71	38.7	58.0		
Fuel EX Carbon Womens High geometry**	14 in	27.5"	35.6	66.5°	9.0	67.7°	54.2	33.8	1.2	43.3	4.3	10.4	108.6	69.1	37.8	56.6		
	15.5 in	27.5"	39.4	66.5°	10.0	67.7°	56.1	33.8	1.2	43.3	4.3	10.4	110.6	69.9	39.4	57.5		
Fuel EX Aluminum Womens Low geometry**	14 in	27.5"	35.6	65.8°	9.0	67.0°	54.4	33.0	2.6	43.4	4.3	10.4	108.8	69.8	37.1	57.1		
	15.5 in	27.5"	39.4	65.8°	10.0	67.0°	56.3	33.0	2.6	43.4	4.3	10.4	110.7	71.1	38.7	58.0		
Fuel EX Aluminum Womens High geometry**	14 in	27.5"	35.6	66.5°	9.0	67.7°	54.2	33.8	1.2	43.3	4.3	10.4	108.6	70.5	37.8	56.6		
	15.5 in	27.5"	39.4	66.5°	10.0	67.7°	56.1	33.8	1.2	43.3	4.3	10.4	110.6	71.8	39.4	57.5		
Remedy Carbon Low geometry**	15.5 in	27.5"	39.4	68.0	9.5	65.5°	56.2	34.9	1.6	43.5	4.6	11.5	114.0	73	39.5	58.7		
	17.5 in	27.5"	41.9	68.0	10.0	65.5°	58.8	34.9	1.6	43.5	4.6	11.5	116.7	76.1	42.0	59.2		
	18.5 in	27.5"	44.5	68.0	10.5	65.5°	60.4	34.9	1.6	43.5	4.6	11.5	118.4	75.8	43.5	59.6		
	19.5 in	27.5"	47.0	68.0	11.0	65.5°	62.5	34.9	1.6	43.5	4.6	11.5	120.6	75.8	45.5	60.1		
	21.5 in	27.5"	52.1	68.0	12.5	65.5°	64.9	34.9	1.6	43.5	4.6	11.5	123.2	76.8	47.5	61.5		

All dimensions are in centimeters unless otherwise stated. Not all sizes are available for all models. Not all sizes are available in all markets.

\*Frame size represents fit. For seat tube length, see column A - Seat tube.

\*\*Refers to high or low setting on adjustable-geometry bikes.







# CITY GEOMETRY

Models	Frame Size*	Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	G - Bottom bracket drop	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover	M - Frame reach	N - Frame stack	Seat height maximum	Seat height minimum
FX 4 5 6	XS	700c	35.6	75.0°	11.0	70.0°	53.1	28.5	6.5	43.8	5.0	74.2	104.5	58.4	38.8	53.3		
	S	700c	40.6	74.5°	13.5	70.5°	55.0	28.5	6.5	43.8	5.0	70.9	105.6	71.2	39.5	55.8		
	M	700c	45.7	74.0°	16.0	71.0°	57.0	28.5	6.5	43.8	5.0	67.6	106.7	74.3	40.3	58.4		
	L	700c	50.8	73.5°	18.5	71.5°	59.0	28.5	6.5	43.8	4.5	69.7	107.2	78.1	40.9	61.1		
FX 1 2 3	XL	700c	55.9	72.5°	21.0	72.5°	62.0	28.5	6.5	43.8	4.5	63.2	108.0	81.8	41.9	64.0		
	S	700c	38.1	74.5°	11.5	70.5°	54.4	28.5	6.2	44.5	5.0	7.0	105.7	69.3	39.4	54.1		
	M	700c	44.4	74.0°	13.0	70.5°	54.8	28.5	6.2	44.5	5.0	7.0	105.7	73.5	38.9	55.5		
	L	700c	50.8	73.5°	16.0	71.5°	56.8	28.5	6.2	44.5	4.5	7.0	105.8	78.3	39.4	58.9		
FX Stagger	XL	700c	57.1	73.0°	19.0	72.5°	59.0	28.5	6.2	44.5	4.5	6.2	106.4	83.1	40.0	62.1		
	XXL	700c	63.5	72.0°	22.0	72.5°	60.3	28.5	6.2	44.5	4.5	6.2	106.5	87.7	39.2	65.0		
	S	700c	38.1	74.5°	13.0	70.5°	54.3	28.5	6.5	44.5	5.0	7.1	105.6	62.7	38.9	55.5		
	M	700c	44.5	74.0°	15.0	70.5°	54.8	28.5	6.5	44.5	5.0	7.1	105.7	63.2	38.3	57.4		
FX 1 2 3 Womens	L	700c	50.8	73.5°	17.0	71.5°	56.8	28.5	6.5	44.5	4.5	7.0	105.7	63.6	39.1	59.8		
	XL	700c	57.2	73.0°	19.0	72.5°	58.5	28.5	6.5	44.5	4.5	6.3	106.3	64.0	40.0	62.1		
	S	700c	33.0	75.0°	11.5	70.0°	53.0	28.5	6.2	44.5	5.0	7.3	105.3	66.6	38.6	53.9		
	M	700c	38.1	75.0°	13.0	70.5°	53.3	28.5	6.2	44.5	5.0	7.0	105.3	69.7	38.4	55.5		
FX 1 2 3 Womens Slagger	L	700c	48.3	74.0°	16.0	70.5°	55.3	28.5	6.2	44.5	5.0	7.0	106.4	76.7	38.6	58.3		
	S	700c	38.1	74.5°	13.0	70.5°	54.3	28.5	6.2	44.5	5.0	7.0	105.6	62.4	38.9	55.5		
	M	700c	44.5	74.0°	15.0	70.5°	54.8	28.5	6.2	44.5	5.0	7.0	105.7	63.0	38.3	57.4		
	L	700c	50.8	73.5°	17.0	71.5°	56.8	28.5	6.2	44.5	4.5	7.0	105.7	63.3	39.1	59.8		
Super Commuter	45 cm	700c	40.0	73.0°	13.0	69.0°	55.9	29.9	6.0	47.0	4.5	8.9	109.6	75.6	38.0	58.6		
	50 cm	700c	45.0	73.0°	15.0	69.5°	57.4	29.9	6.0	47.0	4.5	8.6	110.7	78.9	38.8	60.7		
	55 cm	700c	50.0	73.0°	17.5	70.0°	59.0	29.9	6.0	47.0	4.5	8.3	111.9	81.6	39.7	63.3		
	60 cm	700c	55.0	73.0°	20.5	70.5°	61.3	29.9	6.0	47.0	4.5	7.9	113.8	85.1	41.0	66.3		
Dual Sport Plus	S	700c	35.5	74.5	11.5	70.5	57.5	28.8	6.6	47.3	3.8	7.8	111.4		41	59.8		
	M	700c	42	74	12.5	71	59	28.8	6.6	47.3	3.8	7.5	111.8		41.5	61		
	L	700c	48.3	73	14.0	71	61.2	28.8	6.6	47.3	3.8	7.5	113		42.2	62.4		
	XL	700c	54.6	72.5	15.5	72	63.5	28.8	6.6	47.3	3.8	6.8	113.5		43.2	64.3		
Dual Sport Plus Womens	XS	700c	33	74.5°	11.5	70.0°	55.0	28.8	6.6	47.3	3.8	8.8	108.7		38.4	59.9		
	S	700c	38.1	74.0°	11.5	70.5°	56.0	28.8	6.6	47.3	3.8	8.5	108.8		38.8	60.1		
	M	700c	44.5	73.5°	12.5	71.0°	57.5	28.8	6.6	47.3	3.8	8.2	109		39.4	61.2		
Verve Plus	M	700c	42.0	71.0°	14.7	71.5°	59.7	29.2	7.0	47.5	5.5	6.3	109.6	72.8	39.5	58.7		
	L	700c	47.0	70.5°	14.7	71.5°	60.3	29.2	7.0	47.5	5.5	6.3	109.6	75.5	39.5	58.7		
	XL	700c	53.4	70.0°	16.7	71.5°	61.5	29.2	7.0	47.5	5.5	6.3	110.2	79.7	39.5	60.5		
	XS	700c	34.3	72.0°	14.7	71.0°	56.5	29.2	7.0	47.5	5.5	6.6	108.0	69.5	37.5	58.4		
Dual Sport	S	700c	42.0	71.0°	14.7	71.5°	58.7	29.2	7.0	47.5	5.5	6.3	108.6	73.0	38.5	58.7		
	M	700c	49.5	71.0°	16.7	71.5°	59.9	29.2	7.0	47.5	5.5	6.3	109.7	78.0	39.0	60.5		
	S	700c	38.1	74.5°	11.5	70.0°	57.5	29.4	6.0	45.5	3.8	8.5	109.1	73.8	41	59.5		
	M	700c	44.5	74.0°	12.5	71.0°	59	29.4	6.0	45.5	3.8	8.2	109.5	76.1	41.6	60.6		
Dual Sport Womens	L	700c	50.8	73.5°	13.5	71.0°	60.5	29.4	6.0	45.5	3.8	8.2	110.5	79.1	42.3	61.6		
	XL	700c	57.1	72.5	15.5	72.0	63.5	29.4	6.0	45.5	3.8	7.5	111.0	81.5	43.4	63.9		
	XS	700c	33.0	74.5°	11.5	70.0°	55	29.4	6.0	45.5	3.8	8.9	107.0	69.4	38.5	59.3		
	S	700c	38.1	74.0°	11.5	70.5°	56	29.4	6.0	45.5	3.8	8.5	107.0	71.6	39	59.5		
M	700c	44.5	73.5°	12.5	71.0°	57.5	29.4	6.0	45.5	3.8	8.2	107.5	74.5	39.5	60.6			

All dimensions are in centimeters unless otherwise stated. Not all sizes are available for all models. Not all sizes are available in all markets.  
\*Frame size represents fit. For seat tube length, see column A - Seat tube.

# KIDS' GEOMETRY

Models	Frame Size*	Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	G - Bottom bracket drop	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover	M - Frame reach	N - Frame stack	Seat height maximum	Seat height minimum
Wahoo 26		26"	32.0	74.5°	10.0	70.0°	51.5		4.5	43.0	4.5	7.0	101.7	65.0	37.7	49.9	68.5	89.0
Wahoo 24		24" kids'	29.0	72.0°	10.5	70.0°	52.9		3.8	40.9	4.5	6.1	98.0	60.6	37.3	48.0	67.5	80.0
Wahoo 20		20" kids'	25.5	72.0°	13.5	70.0°	44.5		1.5	37.2	4.2	4.8	86.4	51.8	30.6	42.7	58.5	71.0
Preacliber 16		16" kids'	20.5	70.0°	8.5	70.0°	40.0		1.0	30.4	2.0	5.2	72.2	40.9	27.5	34.2	47.5	58.0
Roscoe 24		24" kids'		72.0°		70.0°	53.2	26.9		41.0		7.1	98.5	60	35.5	54.4		
Roscoe 20		20" kids'		72.0°		70.0°	44.5	23.5		36.3		4.8	86.25	51.75	28.8	48.3		

All dimensions are in centimeters unless otherwise stated. Not all sizes are available for all models. Not all sizes are available in all markets.  
\*Frame size represents fit. For seat tube length, see column A - Seat tube.